



Bureau of Air Quality General Conditional Major Operating Permit

Asphalt Plants

Pursuant to the provisions of the *Pollution Control Act*, Sections 48-1-50(5) and 48-1-110(a), the 1976 *Code of Laws of South Carolina*, as amended, and *South Carolina Regulation 61-62, Air Pollution Control Regulations and Standards*, the Bureau of Air Quality authorizes the operation of these sources in accordance with the valid construction permits, and the plans, specifications and other information submitted in an Operating Permit Application. All official correspondence, plans, permit applications and written statements are an integral part of the permit. Any false information or misrepresentation in the application for a construction or operating permit may be grounds for permit revocation.

The operation of these sources are subject to and conditioned upon the terms, limitations, standards, and schedules contained herein or as specified by this permit and its accompanying attachments.

	Issue Date:	July 15, 2013	
Renewal Due Date:	April 1, 2018	Expiration Date:	June 30, 2018

**Director, Engineering Services Division
Bureau of Air Quality**

ASPHALT PLANTS
Page 2 of 19

RECORD OF REVISIONS	
Date	Description of Change
8/5/2013	Corrected the expiration date and renewal date.
01/16/2014	Clarified some requirements in the permit.
03/13/2015	<p>Template language on Page 1 updated to match other General Conditional Major Permits. Removed Green House Gas limits from conditions A.1 and B.1. Added condition B.6 (general condition for stack tests), Renumbered previous conditions (B.6-B.15 are now B.7-B.16). Modified SO₂ limit in condition B.7 from 3.5 lb/million Btu to 2.3 lb/million Btu. This reflects recent regulation revision. Updated modeling condition C.1. Condition D.7 is now condition F.5. Condition G.3 is now F.3. Added conditions G.1-G.3, renumbered previous conditions (G.1-G.5 are now G.3-G.8). Updated conditions D.4, D.5, D.6, G.6, and G.7 to reflect other permit templates. Changed fonts and formatting throughout the permit for consistency. Added condition B.17.</p>
09/11/2015	<p>Updated condition B.7 (item 2) to add propane due to regulation revision. Updated condition B.10 to clarify applicability of Subpart OOO. Updated condition B.15 to be consistent with other permit templates. Updated condition B.17 to clarify sources are not subject to Standard 5.2 until burner replacement.</p>
12/14/2016	<p>Changed font to Open San. Updated DHEC logo. Updated condition B.1 to include emissions from temporary crushing and screening operations. Updated condition B.17 to incorporate the changes to S. C. Regulation 61-62.5, Standard No. 5.2. Created new Section C to add temporary crushing and screening operation requirements. Renamed the following sections accordingly. Updated condition G.1 to change "no later than" to "within" per updated S.C. Regulation 61-62.1, Section II.</p>

ASPHALT PLANTS
Page 3 of 19

A. APPLICABILITY

Condition Number	Condition
A.1	<p>A facility comprised of asphalt production equipment and the following emission sources: systems for receiving, crushing, screening, handling, storing, weighing, drying, and transferring aggregate (virgin and non-virgin); systems for receiving, storing, and transferring asphalt cement; systems for mixing aggregate with asphalt cement; systems for the storing and dispensing of asphalt; asphalt cement and fuel storage tanks, auxiliary heaters (including hot oil heaters); and associated emission control system or other sources as approved by the Department may operate under the conditions contained herein if it meets all applicable criteria and contains no other significant sources of air emissions.</p> <p>Facilities operating under this general conditional major operating permit must meet all of the following criteria:</p> <ol style="list-style-type: none"> 1. The facility is limited to hot mix asphaltic concrete production or other DOT approved methods as allowed in the permit. Use of any other materials will require Department approval. 2. The maximum size for a single auxiliary heater (including hot oil heaters) is limited to less than 10 million BTU/hr rated input capacity. 3. All fuel fired sources at the facility are limited to using natural gas, propane, liquefied petroleum gas, fuel oil and/or recycled oil (with written approval from the Department) as fuel. No other substances are allowed. 4. Operational restrictions and control device operation will limit emissions below major source thresholds for Title V and Prevention of Significant Deterioration (PSD). Specifically, emissions of all criteria pollutants are less than 100 tons per year (tpy) and less than 250 tpy each, any single hazardous air pollutant (HAP) is less than 10 tpy, any combination of HAP's are less than 25 tpy. 5. The emissions from all batch mix plants (pug mills) must be ducted to the dust control system and baghouse.

B. LIMITATIONS, MONITORING AND REPORTING

Condition Number	Conditions								
B.1	<p>A. (S.C. Regulation 61-62.1, Section II.G and Section II.E) Facility-wide emissions are limited to the following:</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th style="text-align: center;">Pollutant(s)</th> <th style="text-align: center;">Limit</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">PM_{2.5}, PM₁₀, CO, SO₂ NO_x VOC</td> <td style="text-align: center;">Less than 100 tpy Each (12 month rolling sum)</td> </tr> <tr> <td style="text-align: center;">Each Individual HAP</td> <td style="text-align: center;">Less than 10 tpy (12 month rolling sum)</td> </tr> <tr> <td style="text-align: center;">Combined HAP (Sum of each individual HAP)</td> <td style="text-align: center;">Less than 25 tpy (12 month rolling sum)</td> </tr> </tbody> </table>	Pollutant(s)	Limit	PM _{2.5} , PM ₁₀ , CO, SO ₂ NO _x VOC	Less than 100 tpy Each (12 month rolling sum)	Each Individual HAP	Less than 10 tpy (12 month rolling sum)	Combined HAP (Sum of each individual HAP)	Less than 25 tpy (12 month rolling sum)
Pollutant(s)	Limit								
PM _{2.5} , PM ₁₀ , CO, SO ₂ NO _x VOC	Less than 100 tpy Each (12 month rolling sum)								
Each Individual HAP	Less than 10 tpy (12 month rolling sum)								
Combined HAP (Sum of each individual HAP)	Less than 25 tpy (12 month rolling sum)								

ASPHALT PLANTS
Page 4 of 19

B. LIMITATIONS, MONITORING AND REPORTING

Condition Number	Conditions		
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">PM, PM_{2.5}, PM₁₀, CO SO₂, NO_x, VOC</td> <td style="text-align: center;">Less than 250 tpy Each (12 month rolling sum)</td> </tr> </table> <p>Bureau approval must be obtained before the facility may increase emissions over these limits.</p> <p>B. Compliance with the above emission limits shall be demonstrated as follows:</p> <ol style="list-style-type: none"> 1. By limiting asphalt production to no more than 422,000 tons of Asphalt Concrete per rolling year (12 month rolling sum) if the plant is a Batch Mix Asphalt Plant. 2. By limiting asphalt production to no more than 1,220,000 tons of Asphalt Concrete per year (12 month rolling sum) if the plant is a Drum Mix Asphalt Plant. 3. By operating each type of baghouse according to the requirements as specified in this permit. <p>C. The owner/operator shall maintain the following records:</p> <ol style="list-style-type: none"> 1. Daily production records; 2. Baghouse operation records (i.e. pressure drop records, inspection records etc.); and 3. Emergency generator operation records, if applicable. 4. Emissions from temporary crushing and screening operations. <p>D. The owner/operator shall submit semiannual reports that include the following:</p> <ol style="list-style-type: none"> 1. Any baghouse pressure drop exceedances including date and time, magnitude, duration, cause, and corrective actions taken, or a statement that no exceedances occurred. 2. All twelve month rolling sums for asphalt production and emissions from temporary crushing and screening operations. 	PM, PM _{2.5} , PM ₁₀ , CO SO ₂ , NO _x , VOC	Less than 250 tpy Each (12 month rolling sum)
PM, PM _{2.5} , PM ₁₀ , CO SO ₂ , NO _x , VOC	Less than 250 tpy Each (12 month rolling sum)		
B.2	<p>A. Each lime silo shall not be loaded without its baghouse or binvent baghouse on-line and operating properly.</p> <p>B. Each lime silo and fly ash silo baghouse shall be visually inspected for leaks and/or visible emissions in the exhaust while each silo is being loaded. If leaks or visible emissions in the exhaust are present, loading of the silo shall immediately cease until corrective action has been taken.</p> <p>The owner/operator shall record the results of each inspection along with any corrective action taken. The owner/operator shall indicate, in its records, any dates when the source is not in operation. These records shall be maintained on site in written or electronic logs.</p>		
B.3	<p>Each dryer shall not be operated without its dryer baghouse on-line and operating properly.</p> <p>The owner/operator shall continue to operate and maintain a pressure drop gauge on the dryer baghouse. The pressure drop shall be recorded daily during dryer operation.</p> <p>Operation and maintenance checks shall be made on at least a weekly basis for the dryer baghouse cleaning systems, dust collection hoppers and conveying systems for proper operation.</p>		

ASPHALT PLANTS
Page 5 of 19

B. LIMITATIONS, MONITORING AND REPORTING

Condition Number	Conditions
	<p>Pressure drop readings and operation and maintenance checks shall be maintained in logs (written or electronic), along with any corrective action taken when deviations occur. Each incidence of operation outside the operational pressure drop range, including date and time, cause, and corrective action taken, shall be recorded and kept on site. The owner/operator shall indicate, in its records, any dates when the source is not in operation.</p> <p>An operational range for the pressure drop of the dryer baghouse shall be established to provide a reasonable assurance of compliance.</p> <ol style="list-style-type: none"> 1. The operational range for the pressure drop shall be derived by the owner/operator from stack test data, vendor certification, and/or operational history and visual inspections, which demonstrate the proper operation of the equipment in compliance. 2. Once established, the owner/operator shall maintain the established operational range for the pressure drop. 3. The operational range and supporting documentation (for example certification from manufacturer, stack test results, 30 days of normal readings, and/or opacity readings, etc.) shall be submitted to the Director of Engineering Services no later than 180 days from the date coverage is granted under this permit. <p>All dryer baghouse gauges required to be installed shall be readily accessible and easily read by operating personnel and Department personnel (i.e. on ground level or easily accessible roof level).</p> <p>An exceedance of the operational pressure drop range shall not be considered a violation of an emission limit of this permit, unless the exceedance is also accompanied by other information demonstrating that a violation of an emission limit has taken place. Reports of these exceedance incidences shall be submitted semiannually. If no incidences occurred during the reporting period then a statement indicating such shall be included in the semiannual report as stated in condition B.1(D)(1).</p> <p>Any alternative method for monitoring the dryer baghouse performance must be preapproved by the Bureau and shall be incorporated into the permit as set forth in S.C. Regulation 61-62.1 Section II.</p>
B.4	<p>(S.C. Regulation 61-62.5 Standard No.4, Section X.A) All non-enclosed operations shall be conducted in such a manner that a minimum of particulate matter becomes airborne. In no case shall established ambient air quality standards be exceeded at or beyond the property line.</p> <p>Compliance with the requirement above shall be demonstrated by developing a facility-wide fugitive dust control plan (BMP Plan) for controlling fugitive emissions from process operations, truck traffic on roadways owned or controlled by the owner/operator and any other on site operations where fugitive dust emissions can be generated. The plan shall be developed no later than 90 days from the date coverage is granted under this permit, kept on-site and made available to Department personnel upon request. The plan shall contain at a minimum the following requirements as specified in 1 through 15 below. The owner/operator shall implement all of the minimum requirements of the plan listed in this condition immediately upon permit issuance except for item 8 below. The owner/operator may also</p>

ASPHALT PLANTS
Page 6 of 19

B. LIMITATIONS, MONITORING AND REPORTING

Condition Number	Conditions
	<p>modify the plan as needed, maintain a record of revisions on site and make the plan available to Department personnel upon request.</p> <ol style="list-style-type: none"> 1. (S.C. Regulation 61-62.5 Standard No.4, Section X.B and S.C. Regulation 61-62.6, Section III.d) The owner/operator shall maintain dust control of the premises and any roadway it owns or controls by paving, or other suitable measures. Oil treatment is prohibited and volatile organic compounds shall not be used for dust control purposes. 2. The owner/operator shall perform daily visual inspections during normal plant operation of equipment loading/unloading areas, any mixing areas and any air pollution control equipment. Visual inspection means a qualitative observation of opacity during daylight. The observer does not need to be certified to conduct valid visual inspections. However, at a minimum, the observer should be experienced and knowledgeable about the effects on visibility of emissions caused by background contrast, ambient lighting, and observer position relative to lighting, wind, and the presence of uncombined water. Daily inspections must be documented by a written or electronic record which includes the date and time performed, noting color, duration, density (heavy or light), cause and corrective action taken for any abnormal emissions, the inspector's name or initials and the operating conditions of the equipment. 3. If dust suppressant aids are used then they shall be applied according to the manufacturer specifications for quantity and frequency. 4. Spillage and residual materials that have the potential for creating emissions problems shall be removed at an appropriate frequency to minimize levels of fugitive dust emissions. 5. Haul road speed limits shall be imposed where necessary. 6. The asphalt plant shall be configured to minimize front-end loader and truck travel distances. 7. If applicable, water trucks shall be operated at an appropriate frequency to minimize levels of fugitive dust emissions. The owner/operator may adjust the water truck operation as necessary to accommodate weather conditions. 8. If applicable, written guidelines for water trucks shall be developed for water truck operators on how to handle water truck failures including a back-up scenario for when it fails or is inadequate. 9. If applicable, weekly inspections of all water trucks in use to control fugitive dust emissions shall be made and proper maintenance performed if needed on the vehicle. Vehicle inspections shall be recorded and include all problems, corrective actions and maintenance activities. 10. Engineering design, inherent moisture content in the aggregate and/or asphalt coating on recycled asphalt shall be used to control fugitive emissions at the following points: delumpers, screening operations, conveying systems and material handling systems up to the storage bins, including aggregate piles. Wet suppression shall be used to augment the inherent moisture as needed for operations up to the storage bins and including aggregate piles. Owner/operators shall be trained to handle process upsets and to maintain general housekeeping practices as necessary to minimize fugitive emissions. 11. Free fall transfer drop points shall be minimized where necessary. 12. The owner/operator shall notify vendors and suppliers in writing that all vendors must cover their material with a tarp when delivering materials to the facility.

ASPHALT PLANTS
Page 7 of 19

B. LIMITATIONS, MONITORING AND REPORTING

Condition Number	Conditions																		
	<p>13. The owner/operator shall document and review plant operations and make any changes as necessary regarding plant-wide fugitive emissions.</p> <p>14. The owner/operator shall conduct annual training for current and new employees on dust control operation procedures to include reviewing all physical controls and maintenance schedules.</p> <p>15. In the event of a dust control equipment failure, the owner/operator shall repair or replace dust control equipment with readily available parts.</p>																		
B.5	<p>(S.C. Regulation 61-62.5, Standard No.4, Section VI) Particulate matter and opacity emissions from asphalt manufacturing shall be limited to the following:</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th style="text-align: center;">Production Rate (tph)</th> <th style="text-align: center;">Maximum Allowable PM Emission Rate (lb/hr)</th> </tr> </thead> <tbody> <tr><td style="text-align: center;">20</td><td style="text-align: center;">22</td></tr> <tr><td style="text-align: center;">50</td><td style="text-align: center;">31</td></tr> <tr><td style="text-align: center;">100</td><td style="text-align: center;">38</td></tr> <tr><td style="text-align: center;">150</td><td style="text-align: center;">45</td></tr> <tr><td style="text-align: center;">200</td><td style="text-align: center;">51</td></tr> <tr><td style="text-align: center;">250</td><td style="text-align: center;">56</td></tr> <tr><td style="text-align: center;">300</td><td style="text-align: center;">61</td></tr> <tr><td style="text-align: center;">Greater than 350</td><td style="text-align: center;">65</td></tr> </tbody> </table> <p>The maximum allowable PM emission rate for facilities with production rates between two points listed in the table above shall be determined through interpolation. The particulate matter emission rate limit determined above shall apply to entire facility as a whole. All particulate matter emissions from the facility must be below this limit.</p> <p>The opacity limit is 20% for all production rates.</p> <p>Compliance with the above emission limits shall be demonstrated as follows:</p> <ol style="list-style-type: none"> 1. By operating the dryer baghouse as specified in this permit. 2. (S.C. Regulation 61-62.5, Standard No.4 Section XII) By performing a scheduled periodic test for particulate matter emissions every two years and conducting the test in accordance with S.C. Regulation 61-62.1, Section IV. 3. During the periodic test, the owner/operator is required to produce a South Carolina Department of Transportation (SCDOT) specification surface mix. The Department may, at its discretion, waive this requirement if sufficient evidence indicates that less than 25% of the plant's total annual production is surface mix. 4. The periodic test shall be conducted while the plant is operating at its maximum production rate. Plants testing at less than maximum rated production may have their production rate limited as determined by "Asphalt Plant Aggregate Moisture vs. Hot Mix Asphalt Production Potential Guidance" of March 15, 2001, as amended. Retests shall be required to exceed a limit established by the last periodic test. Retests may also be required if facilities exceed their maximum allowable production rate. 	Production Rate (tph)	Maximum Allowable PM Emission Rate (lb/hr)	20	22	50	31	100	38	150	45	200	51	250	56	300	61	Greater than 350	65
Production Rate (tph)	Maximum Allowable PM Emission Rate (lb/hr)																		
20	22																		
50	31																		
100	38																		
150	45																		
200	51																		
250	56																		
300	61																		
Greater than 350	65																		

ASPHALT PLANTS
Page 8 of 19

B. LIMITATIONS, MONITORING AND REPORTING

Condition Number	Conditions												
	<p>5. The periodic test shall be conducted on a virgin aggregate mix or Reclaimed Asphalt Pavement (RAP) up to the maximum percent of aged binder allowable per SCDOT's RAP Specification.</p> <p>6. The percent (%) moisture of the aggregate shall be obtained for each test series.</p>												
B.6	<p>For any source test required under an applicable standard or permit condition, the owner, operator, or representative shall comply with S.C. Regulation 61-62.1, Section IV - Source Tests.</p> <p>Unless approved otherwise by the Department, the owner, operator, or representative shall ensure that source tests are conducted while the source is operating at the maximum expected production rate or other production rate or operating parameter which would result in the highest emissions for the pollutants being tested. Some sources may have to spike fuels or raw materials to avoid being subjected to a more restrictive feed or process rate. Any source test performed at a production rate less than the rated capacity may result in permit limits on emission rates, including limits on production if necessary.</p> <p>The owner or operator shall comply with any limits that result from conducting a source test at less than rated capacity. A copy of the most recent Department issued source test summary letter, whether it imposes a limit or not, shall be maintained with the operating permit, for each source that is required to conduct a source test.</p> <p>Site-specific test plans and amendments, notifications, and source test reports shall be submitted to the Manager of the Source Evaluation Section, Bureau of Air Quality.</p>												
B.7	<p>(S.C. Regulation 61-62.5, Standard No.1) Each auxiliary heater (including hot oil heaters) are subject to the following limitations:</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th style="text-align: center;">Heater Construction Date</th> <th style="text-align: center;">Opacity Limit</th> <th style="text-align: center;">PM Limit (lb/million Btu Heat Input)</th> <th style="text-align: center;">SO₂ Limit (lb/million Btu Heat Input)</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">On or after February 11, 1971</td> <td style="text-align: center;">20%</td> <td style="text-align: center;">0.6</td> <td style="text-align: center;">2.3</td> </tr> <tr> <td style="text-align: center;">Before February 11, 1971</td> <td style="text-align: center;">40%</td> <td style="text-align: center;">0.8*</td> <td style="text-align: center;">2.3</td> </tr> </tbody> </table> <p>*≤ 10 million Btu/hr</p> <p>Compliance with the limits above shall be demonstrated as follows:</p> <ol style="list-style-type: none"> 1. To the extent practicable, by maintaining and operating the heater in a manner consistent with good air pollution control practices for minimizing emissions. 2. Except for natural gas and propane fired units, by maintaining a log of the time, magnitude, duration and any other pertinent information to determine periods of startup and shutdown of the heater and make these records available to a Department representative upon request. 	Heater Construction Date	Opacity Limit	PM Limit (lb/million Btu Heat Input)	SO ₂ Limit (lb/million Btu Heat Input)	On or after February 11, 1971	20%	0.6	2.3	Before February 11, 1971	40%	0.8*	2.3
Heater Construction Date	Opacity Limit	PM Limit (lb/million Btu Heat Input)	SO ₂ Limit (lb/million Btu Heat Input)										
On or after February 11, 1971	20%	0.6	2.3										
Before February 11, 1971	40%	0.8*	2.3										
B.8	<p>(S.C. Regulation 61-62.5, Standard 3 and S.C. Regulation 61-62.1 Section I Definition 93(a)) For facilities that have the authorization from the Department to burn specification oil as fuel, each batch of specification oil must meet the following specifications:</p>												

ASPHALT PLANTS
Page 9 of 19

B. LIMITATIONS, MONITORING AND REPORTING

Condition Number	Conditions																
	<table border="1" style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <thead> <tr style="background-color: #d3d3d3;"> <th style="width: 30%; text-align: center;">Parameter</th> <th style="text-align: center;">Specification</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Arsenic</td> <td style="text-align: center;">5 ppm maximum</td> </tr> <tr> <td style="text-align: center;">Cadmium</td> <td style="text-align: center;">2 ppm maximum</td> </tr> <tr> <td style="text-align: center;">Chromium</td> <td style="text-align: center;">10 ppm maximum</td> </tr> <tr> <td style="text-align: center;">Lead</td> <td style="text-align: center;">100 ppm maximum</td> </tr> <tr> <td style="text-align: center;">Nickel</td> <td style="text-align: center;">120 ppm maximum</td> </tr> <tr> <td style="text-align: center;">Total Halogens</td> <td style="text-align: center;">1,000 ppm maximum</td> </tr> <tr> <td style="text-align: center;">Flash Point</td> <td style="text-align: center;">100°F (37.8°C) minimum</td> </tr> </tbody> </table> <p>Compliance with the oil specifications shall be demonstrated as follows:</p> <ol style="list-style-type: none"> 1. By maintaining for each shipment of specification oil received from off-site, a record of the date and total amount of oil received. 2. By maintaining for on-site generated specification oil, a record of the amount generated and the dates on which it was burned. 3. By maintaining a record of a lab analysis for on-site generated oil that shows the total arsenic, total cadmium, total chromium, total lead, total nickel, total halogens and flash point. 4. By maintaining a waste analysis showing the total arsenic, total cadmium, total chromium, total lead, total nickel, total halogens and flash point. The waste analysis shall be performed only on the initial shipment of oil unless the oil becomes inconsistent in composition or is received from another supplier. 	Parameter	Specification	Arsenic	5 ppm maximum	Cadmium	2 ppm maximum	Chromium	10 ppm maximum	Lead	100 ppm maximum	Nickel	120 ppm maximum	Total Halogens	1,000 ppm maximum	Flash Point	100°F (37.8°C) minimum
Parameter	Specification																
Arsenic	5 ppm maximum																
Cadmium	2 ppm maximum																
Chromium	10 ppm maximum																
Lead	100 ppm maximum																
Nickel	120 ppm maximum																
Total Halogens	1,000 ppm maximum																
Flash Point	100°F (37.8°C) minimum																
B.9	<p>Each asphalt facility is subject to New Source Performance Standards (NSPS), 40CFR60 Subpart A, General Conditions and Subpart I, Standards of Performance For Asphalt Concrete Plants, and S.C. Regulation 61-62.60 Subparts A and Subpart I, Standards of Performance For Asphalt Concrete Plants, as applicable. These sources shall comply with all applicable requirements of Subparts A and I.</p> <p>(40CFR60.92.a) Each Asphalt Facility shall meet the limits specified in the following table:</p> <table border="1" style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <thead> <tr style="background-color: #d3d3d3;"> <th style="width: 30%; text-align: center;">Opacity Limit</th> <th style="text-align: center;">PM Limit</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">20%</td> <td style="text-align: center;">90 mg/dscm (0.04 gr/dscf)</td> </tr> </tbody> </table> <p>Compliance shall be demonstrated by operating the dryer baghouse as specified in this permit.</p>	Opacity Limit	PM Limit	20%	90 mg/dscm (0.04 gr/dscf)												
Opacity Limit	PM Limit																
20%	90 mg/dscm (0.04 gr/dscf)																
B.10	<p>Each affected source is subject to New Source Performance Standards (NSPS), 40CFR60 Subpart A, General Conditions and Subpart OOO, Standards of Performance For Nonmetallic Mineral Processing Plants, and S.C. Regulation 61-62.60 Subparts A and Subpart OOO, Nonmetallic Mineral Processing Plants, as applicable. These sources shall comply with all applicable requirements of Subparts A and OOO.</p> <p>(40CFR60 Subpart OOO) Each RAP crusher, screen, and conveyor listed in the Table below shall meet the opacity limit specified for it:</p>																

ASPHALT PLANTS
Page 10 of 19

B. LIMITATIONS, MONITORING AND REPORTING

Condition Number	Conditions												
	<p>(40CFR60.671) Crusher means a machine used to crush any nonmetallic minerals, and includes, but is not limited to, the following types: Jaw, gyratory, cone, roll, rod mill, hammermill, and impactor.</p> <p>(40CFR60.671) Screening operation means a device for separating material according to size by passing undersize material through one or more mesh surfaces (screens) in series, and retaining oversize material on the mesh surfaces (screens). Grizzly feeders associated with truck dumping and static (non-moving) grizzlies used anywhere in the nonmetallic mineral processing plant are not considered to be screening operations.</p> <p>(40CFR60.671) Conveying system means a device for transporting materials from one piece of equipment or location to another location within a plant. Conveying systems include but are not limited to the following: feeders, belt conveyors, bucket elevators and pneumatic systems.</p> <table border="1" style="margin: 10px auto; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Crusher Manufacture Date</th> <th style="text-align: center;">Crusher Opacity Limit</th> <th style="text-align: center;">Screen Opacity Limit</th> <th style="text-align: center;">Conveyor Opacity Limit</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">After August 31, 1983 but before April 22, 2008</td> <td style="text-align: center;">15%</td> <td style="text-align: center;">10%</td> <td style="text-align: center;">10% from each transfer point</td> </tr> <tr> <td style="text-align: center;">After April 22, 2008</td> <td style="text-align: center;">12%</td> <td style="text-align: center;">7%</td> <td style="text-align: center;">7% from each transfer point</td> </tr> </tbody> </table> <p>RAP fractionating equipment (lumpbreakers and associated screen conveying system) that do not resize any aggregate or nonmetallic mineral embedded in the RAP is not subject to this regulation.</p> <p>Compliance with the above emission limits shall be demonstrated as follows:</p> <ol style="list-style-type: none"> 1. (40CFR60.8) By conducting a one time performance test for opacity within 60 days after achieving the maximum production rate at which RAP crusher, screen, and conveyor will be operated, but not later than 180 days after initial startup of the RAP crusher, screen, and conveyor. The test shall be conducted according to the requirements of 40CFR60.11, 40CFR60.675 (Table 3 of 40CFR60 Subpart OOO) and S.C. Regulation 61-62.1 Section IV. 2. By performing daily visual emission checks on the RAP crusher, screen, and conveyor when in operation. 3. By the proper operation of the air pollution control device if the RAP crusher, screen, and conveyor is equipped with one. <p>RAP replacement equipment shall comply with the requirements of 40CFR60.672.d and S.C. Regulation 61-62 .1 Section II.A.1.b.</p>	Crusher Manufacture Date	Crusher Opacity Limit	Screen Opacity Limit	Conveyor Opacity Limit	After August 31, 1983 but before April 22, 2008	15%	10%	10% from each transfer point	After April 22, 2008	12%	7%	7% from each transfer point
Crusher Manufacture Date	Crusher Opacity Limit	Screen Opacity Limit	Conveyor Opacity Limit										
After August 31, 1983 but before April 22, 2008	15%	10%	10% from each transfer point										
After April 22, 2008	12%	7%	7% from each transfer point										

ASPHALT PLANTS
Page 11 of 19

B. LIMITATIONS, MONITORING AND REPORTING

Condition Number	Conditions						
B.11	All fuel fired sources at the facility are limited to using natural gas, propane, liquefied petroleum gas, virgin fuel oil and/or recycled oil (with prior written approval from the Department) as fuel. No other substances are allowed.						
B.12	The use of materials, other than virgin aggregate or reclaimed asphalt pavement, as aggregate shall not be allowed without prior written approval from the Department.						
B.13	The production of asphalt concrete other than hot mix asphalt (e.g. other DOT approved methods, warm mix asphalt), is allowed without prior approval from the Department.						
B.14	(40CFR60.11.d) At all times, including periods of startup, shutdown, and malfunction, the owner/operator shall, to the extent practicable, maintain and operate the equipment including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to the Department which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source.						
B.15	Emergency power generators less than or equal to 150 kilowatt (kW) rated capacity or greater than 150 kW rated capacity designated for emergency use only and operated a total of 500 hours per year or less for testing and maintenance with a method to record the actual hours of use such as an hour meter have been determined to be exempt from construction permitting requirements in accordance with South Carolina Regulation 61-62.1. These sources shall still comply with the requirements of all applicable regulations including but not limited to the following: New Source Performance Standards (NSPS) 40 CFR 60 Subpart A (General Provisions); NSPS 40 CFR 60 Subpart IIII (Stationary Compression Ignition Internal Combustion Engines); NSPS 40 CFR 60 Subpart JJJJ (Stationary Spark Ignition Internal Combustion Engines); National Emission Standards for Hazardous Air Pollutants (NESHAP) 40 CFR 63 Subpart A (General Provisions); and NESHAP 40 CFR 63 Subpart ZZZZ (Stationary Reciprocating Internal Combustion Engines).						
B.16	(S.C. Regulation 61-62.5, Standard No. 4, Section IX) For all other sources where an opacity limit is not specified, each shall meet the following opacity limits: <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th style="text-align: center;">Construction or Modification Date</th> <th style="text-align: center;">Opacity Limit</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Began after December 31, 1985</td> <td style="text-align: center;">20%</td> </tr> <tr> <td style="text-align: center;">Began on or before December 31, 1985</td> <td style="text-align: center;">40%</td> </tr> </tbody> </table> <p>Compliance with the above emission limits shall be demonstrated by complying with the Fugitive Dust Control Plan.</p>	Construction or Modification Date	Opacity Limit	Began after December 31, 1985	20%	Began on or before December 31, 1985	40%
Construction or Modification Date	Opacity Limit						
Began after December 31, 1985	20%						
Began on or before December 31, 1985	40%						
B.17	(S. C. Regulation 61-62.5, Standard No. 5.2) Any existing source where a burner assembly is replaced with another burner assembly after June 25, 2004, regardless of size or age of the burner assembly to be replaced shall be replaced with a low NO _x burner assembly or equivalent technology, and shall achieve a 30 percent reduction from uncontrolled NO _x emission levels based upon manufacturer's specifications. An exemption from this requirement shall be granted when a single burner assembly is						

ASPHALT PLANTS
Page 12 of 19

B. LIMITATIONS, MONITORING AND REPORTING

Condition Number	Conditions
	<p>being replaced in an existing source with multiple burners due to non-routine maintenance. The replacement of individual components such as burner heads, nozzles, or windboxes does not trigger this requirement.</p> <p>The owner or operator shall notify and register the burner assembly replacement with the Department, in writing, within 7 days of replacing the existing burner assembly. Notification will be provided on the Department's <i>Low NO_x Burner Assembly Replacement Notification</i> Form D-2935. Those affected sources that wish to receive an emission reduction credit for the control device will be required to submit a construction permit application. Those affected sources requesting an alternative control methodology must receive written approval prior to burner replacement.</p> <p>The owner or operator shall perform tune-ups every twenty-four (24) months in accordance with manufacturer's specifications or with good engineering practices. The first tune-up shall be conducted no more than twenty-four (24) months from replacement of a burner assembly for affected existing sources. Each subsequent tune-up shall be conducted no more than twenty-four (24) months after the previous tune-up.</p> <p>All tune-up records are required to be maintained on site and available for inspection by the Department for a period of five (5) years from the date generated.</p> <p>The owner or operator shall develop and retain a tune-up plan on file.</p>

C. TEMPORARY CRUSHING AND SCREENING OPERATION CONDITIONS

Condition Number	Condition
C.1	<p>Temporary crushing and screening operation equipment may include following emission sources: crushers, grinding mills, screening operations, bucket elevators, belt conveyors, bagging operations, storage bins, enclosed truck or railcar loading stations and associated emission control system or other sources as approved by the Department. The owner/operator may operate a temporary crushing and/or screening operation in conjunction with the asphalt plant under the conditions herein if it meets the following criteria:</p> <ol style="list-style-type: none"> 1. The equipment processes nonmetallic minerals only. 2. Wet suppression is always used during crushing operation. This includes ground and spray bars as needed. 3. The equipment is portable or transportable and does not reside at any one site for more than 12 consecutive months. A site is one or more contiguous or adjacent properties that are under common control. If plants are co-located, emissions from both plants and crushing/screening operations have to be combined. The amount of time that equipment is kept in storage does not count towards the 12 month residence time requirement. Equipment in storage shall be placed in a separate storage location within the facility and not set up in an operational

ASPHALT PLANTS
Page 13 of 19

C. TEMPORARY CRUSHING AND SCREENING OPERATION CONDITIONS

Condition Number	Condition
	<p>configuration. Equipment set up at a location ready to operate, shall count towards the 12 month time period, even if it is not turned on.</p> <p>4. The diesel engines are fired on low sulfur (500 ppm or less) diesel/No. 2 fuel oil with a maximum sulfur content of 0.05 weight %.</p> <p>5. The diesel engines are certified by the manufacturer to meet EPA's nonroad diesel engine emission standards/tiers (40 CFR 89 and 1039).</p>
C.2	Diesel engines are limited to operating a maximum of 500 hours per year per location in order to be considered exempt from air dispersion modeling requirements. The owner or operator must record the actual operating hours with an hour meter or other equivalent method.
C.3	(Stationary Internal Combustion Engines constructed after June 25, 2004) Owners or operators shall perform tune-ups every two years in accordance with manufacturer's specifications or with good engineering practices. All tune-up records are required to be maintained on site. The facility shall develop and retain a tune-up plan on file.
C.4	<p>Stationary Internal Combustion engines shall comply with the requirements of all applicable regulations including but not limited to:</p> <p>New Source Performance Standard (NSPS) 40 CFR 60 Subparts A (General Provisions); IIII (Stationary Compression Ignition Internal Combustion Engines); and National Emission Standards for Hazardous Air Pollutants (NESHAP) 40 CFR 63 Subparts A (General Provisions) and ZZZZ (Reciprocating Internal Combustion Engines).</p>
C.5	<p>Aggregate Processing</p> <p>(S.C. Regulation 61-62.5, Standard No. 4, Section VIII) Particulate matter emissions shall be limited to the rate specified by use of the following equations:</p> <p style="padding-left: 40px;">For process weight rates less than or equal to 30 tons per hour $E = (F) 4.10P^{0.67}$ and</p> <p style="padding-left: 40px;">For process weight rates greater than 30 tons per hour $E = (F) 55.0P^{0.11} - 40$</p> <p style="padding-left: 40px;">Where E = the allowable emission rate in pounds per hour P = process weight rate in tons per hour F = effect factor from Table B in S.C. Regulation 61-62.5, Standard No. 4</p>
C.6	<p>(S.C. Regulation 61-62.5, Standard No. 4, Section IX) Where construction or modification began on or before December 31, 1985, emissions from these sources (including fugitive emissions) shall not exhibit an opacity greater than 40%.</p> <p>(S.C. Regulation 61-62.5, Standard No. 4, Section IX) Where construction or modification began after December 31, 1985, emissions from these sources (including fugitive emissions) shall not exhibit an opacity greater than 20%.</p>
C.7	(S.C. Regulation 61-62.5, Standard No. 4, Section X) All non-enclosed operations shall be conducted in such a manner that a minimum of particulate matter becomes airborne. In no case shall established ambient air quality standards be exceeded at or beyond the property line. The owner/operator of all

ASPHALT PLANTS
Page 14 of 19

C. TEMPORARY CRUSHING AND SCREENING OPERATION CONDITIONS

Condition Number	Condition								
	<p>such operations shall maintain dust control of the premises and any roadway owned or controlled by the owner/operator by paving or other suitable measures. Oil treatment is prohibited.</p> <p>(SC Regulation 61-62.6 Section III.a) Emissions of fugitive particulate matter shall be controlled in such a manner and to the degree that it does not create an undesirable level of air pollution.</p> <p>(SC Regulation 61-62.6 Section III.b) Restrictions and requirements may be contained in operating permits on a case-by-case basis that are deemed appropriate and necessary to control fugitive particulate matter in accordance with reasonably available control technology.</p> <p>(SC Regulation 61-62.6 Section III.c) Any method of materials handling which will generate fugitive particulate matter that is not fully described in the permit application shall not be used.</p>								
C.8	When unfavorable metrological conditions (i.e., dry and very windy) create particulate matter emissions from the operation that exceed opacity limits, the permittee cease operation until the conditions have ceded or additional controls (e.g., extra water sprays, wind screens) have been added that bring the emissions to compliant levels.								
C.9	This facility is subject to the provisions of 40 CFR Part 60, New Source Performance Standards General Provisions, Subparts A, Standards of Performance for Nonmetallic Mineral Processing Plants, Subpart OOO. Existing affected sources shall comply with the applicable provisions by the compliance date specified in Subparts OOO. Any new affected sources shall comply with the requirements of these Subparts upon initial start-up unless otherwise noted.								
C.10	In accordance with S.C. Regulation 61-62.60 & 40 CFR 60 – New Source Performance Standards (NSPS) Subpart OOO - Standards of Performance for Nonmetallic Mineral Processing Plants, the equipment (excluding diesel engines) manufactured after August 31, 1983, used by owner/operators that employ a portable crusher with a manufacturer’s rating of greater than 150 ton/hr or a non-portable crusher with a manufacturer’s rating of greater than 25 ton/hr are subject to NSPS Subpart OOO.								
C.11	<p>Standards for PM (40 CFR 60 Subparts A and OOO) In accordance with 40 CFR 60.672(b), affected facilities must meet the fugitive emission limits and compliance requirements in Table 3 of this subpart within 60 days after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup as required under 40 CFR 60.11. The requirements in Table 3 of this subpart apply for fugitive emissions from affected facilities without capture systems and for fugitive emissions escaping capture systems.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 5px;">The owner or operator must meet the following fugitive emissions limit and must demonstrate compliance with these limits by conducting performance tests as listed below for:</td> </tr> <tr> <td colspan="2" style="padding: 5px;">Grinding mills, screening operations, bucket elevators, transfer points on belt conveyors, bagging operations, storage bins, enclosed truck or railcar loading stations or from any other affected facility.</td> </tr> <tr> <td style="text-align: center; padding: 5px;">Affected facilities that commenced construction, modification, or reconstruction after August 31, 1983 but before April 22, 2008</td> <td style="text-align: center; padding: 5px;">Affected facilities that commence construction, modification, or reconstruct on or after April 22, 2008</td> </tr> <tr> <td style="text-align: center; padding: 5px;">10 percent opacity</td> <td style="text-align: center; padding: 5px;">7 percent opacity</td> </tr> </table>	The owner or operator must meet the following fugitive emissions limit and must demonstrate compliance with these limits by conducting performance tests as listed below for:		Grinding mills, screening operations, bucket elevators, transfer points on belt conveyors, bagging operations, storage bins, enclosed truck or railcar loading stations or from any other affected facility.		Affected facilities that commenced construction, modification, or reconstruction after August 31, 1983 but before April 22, 2008	Affected facilities that commence construction, modification, or reconstruct on or after April 22, 2008	10 percent opacity	7 percent opacity
The owner or operator must meet the following fugitive emissions limit and must demonstrate compliance with these limits by conducting performance tests as listed below for:									
Grinding mills, screening operations, bucket elevators, transfer points on belt conveyors, bagging operations, storage bins, enclosed truck or railcar loading stations or from any other affected facility.									
Affected facilities that commenced construction, modification, or reconstruction after August 31, 1983 but before April 22, 2008	Affected facilities that commence construction, modification, or reconstruct on or after April 22, 2008								
10 percent opacity	7 percent opacity								

ASPHALT PLANTS
Page 15 of 19

C. TEMPORARY CRUSHING AND SCREENING OPERATION CONDITIONS

Condition Number	Condition	
	An initial performance test according to 40 CFR 60.11 of this part and 40 CFR 60.675 of this subpart	<p>An initial performance test according to 40 CFR 60.11 and 40 CFR 60.675; and Periodic inspections of water sprays according to 40CFR 60.674(b) and 60.676(b);</p> <p>A repeat performance test according to 40 CFR 60.11 of this part and 40 CFR 60.675 within 5 years from the previous performance test for fugitive emissions from affected facilities without water sprays. Affected facilities controlled by water carryover from upstream water sprays that are inspected according to the requirements in 40 CFR 60.674(b) and 60.676(b) are exempt from this 5-year repeat testing requirement.</p>
<p>The owner or operator must meet the following fugitive emissions limit and must demonstrate compliance with these limits by conducting performance tests as listed below for:</p> <p>Crushers at which a capture system is not used.</p>		
Affected facilities that commenced construction, modification, or reconstruction after August 31, 1983 but before April 22, 2008		Affected facilities that commence construction, modification, or reconstruct on or after April 22, 2008
15 percent opacity		12 percent opacity
	An initial performance test according to 40 CFR 60.11 of this part and 40 CFR 60.675 of this subpart	<p>An initial performance test according to 40 CFR 60.11 and 40 CFR 60.675; and Periodic inspections of water sprays according to 40CFR 60.674(b) and 60.676(b);</p> <p>A repeat performance test according to 40 CFR 60.11 of this part and 40 CFR 60.675 within 5 years from the previous performance test for fugitive emissions from affected facilities without water sprays. Affected facilities controlled by water carryover from upstream water sprays that are inspected according to the requirements in 40 CFR 60.674(b) and 60.676(b) are exempt from this 5-year repeat testing requirement.</p>
<p>Due to the temporary nature of equipment, the initial performance test shall be conducted prior to the equipment being removed from the site of its first operation in this state.</p>		

ASPHALT PLANTS
Page 16 of 19

D. AMBIENT AIR STANDARDS REQUIREMENTS

Condition Number	Condition
D.1	<p>Air dispersion modeling (or other method) has demonstrated that this facility's operation will not interfere with the attainment and maintenance of any state or federal ambient air standard. Any changes in the parameters used in this demonstration may require a review by the facility to determine continuing compliance with these standards. These potential changes include any decrease in stack height, decrease in stack velocity, increase in stack diameter, decrease in stack exit temperature, increase in building height or building additions, increase in emission rates, decrease in distance between stack and property line, changes in vertical stack orientation, and installation of a rain cap that impedes vertical flow. Parameters that are not required in the determination will not invalidate the demonstration if they are modified. The emission rates used in the determination are listed in Attachment - Emission Rates for Ambient Air Standards of this permit. Higher emission rates may be administratively incorporated into Attachment - Emission Rates for Ambient Air Standards of this permit provided a demonstration using these higher emission rates shows the attainment and maintenance of any state or federal ambient air quality standard or with any other applicable requirement. Variations from the input parameters in the demonstration shall not constitute a violation unless the maximum allowable ambient concentrations identified in the standard are exceeded.</p> <p>The owner/operator shall maintain this facility at or below the emission rates as listed in Attachment - Emission Rates for Ambient Air Standards, not to exceed the pollutant limitations of this permit. Should the facility wish to increase the emission rates listed in Attachment - Emission Rates for Ambient Air Standards, not to exceed the pollutant limitations in the body of this permit, it may do so by the administrative process specified above. This is a State Only enforceable requirement.</p>

E. GENERAL RECORD KEEPING AND REPORTING

Condition Number	Conditions
E.1	Reporting required in this permit, shall be submitted in a timely manner. Semiannual reports are due January 30 th and July 30 th each year.
E.2	<p>All reports and notifications required under this permit shall be submitted to the person indicated in the specific condition at the following address:</p> <p style="text-align: center;">2600 Bull Street Columbia, SC 29201</p> <p>The contact information for the local EQC Regional office can be found at: http://www.scdhec.gov</p>
E.3	Unless elsewhere specified within this permit, all reports required under this permit shall be submitted to the Manager of the Technical Management Section, Bureau of Air Quality.

ASPHALT PLANTS
Page 17 of 19

E. GENERAL RECORD KEEPING AND REPORTING

Condition Number	Conditions
E.4	(S.C. Regulation 61-62.1, Section II.J.1.g) A copy of the Department issued construction and/or operating permit must be kept readily available at the facility at all times. The owner or operator shall maintain such operational records; make reports; install, use, and maintain monitoring equipment or methods; sample and analyze emissions or discharges in accordance with prescribed methods at locations, intervals, and procedures as the Department shall prescribe; and provide such other information as the Department reasonably may require. All records required to demonstrate compliance with the limits established under this permit shall be maintained on site for a period of at least 5 years from the date the record was generated and shall be made available to a Department representative upon request.
E.5	The owner/operator shall inspect, calibrate, adjust, and maintain continuous monitoring systems, monitoring devices, and gauges in accordance with manufacturer's specifications or good engineering practices. The owner or operator shall maintain on file all measurements including continuous monitoring system or monitoring device performance measurements; all continuous monitoring system performance evaluations; all continuous monitoring system or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; and all other information required in a permanent form suitable for inspection by Department personnel.
E.6	<p>(S.C. Regulation 61-62.1, Section II.J) For sources not required to have continuous emissions monitors, any malfunction of air pollution control equipment or system, process upset or other equipment failure which results in discharges of air contaminants lasting for one hour or more and which are greater than those discharges described for normal operation in the permit application shall be reported to the Department's local Environmental Quality Control Regional office within 24 hours after the beginning of the occurrence.</p> <p>The owner or operator shall also submit a written report within 30 days of the occurrence. This report shall be submitted to the Manager of the Technical Management Section, Bureau of Air Quality and shall include, at a minimum, the following:</p> <ol style="list-style-type: none"> 1. The identity of the stack and/or emission point where the excess emissions occurred; 2. The magnitude of excess emissions expressed in the units of the applicable emission limitation and the operating data and calculations used in determining the excess emissions; 3. The time and duration of excess emissions; 4. The identity of the equipment causing the excess emissions; 5. The nature and cause of such excess emissions; 6. The steps taken to remedy the malfunction and the steps taken or planned to prevent the recurrence of such malfunction; 7. The steps taken to limit the excess emissions; and, 8. Documentation that the air pollution control equipment, process equipment, or processes were at all times maintained and operated, to the maximum extent practicable, in a manner consistent with good practice for minimizing emissions.

ASPHALT PLANTS
Page 18 of 19

F. RELOCATION REQUIREMENTS

Condition Number	Condition
F.1	The owner/operator must submit an application that includes air dispersion modeling and gain approval from this Department prior to relocating this plant to any other site in South Carolina.
F.2	The owner/operator may move a plant out of South Carolina without gaining prior approval. Notification that the plant was moved out of South Carolina shall be made within 30 days of such a move. Department approval must be gained prior to bringing the plant back into South Carolina.

G. PERMIT RENEWAL, MODIFICATION, EXPIRATION, AND TRANSFER OF OWNERSHIP

Condition Number	Condition
G.1	(S.C. Regulation 61-62.1, Section II.H) The owner/operator shall submit an operating permit renewal request to the Department within 90 days prior to the operating permit expiration date. The operating permit renewal requests shall include a description of any changes at the facility that have occurred since issuance of the last operating permit that may affect the operating permit or operating permit review. In general, the description shall include any addition, alteration or removal of sources, including sources exempt from construction permit requirements; addition, alteration or removal of emission limitations; any changes to monitoring, recordkeeping, or reporting requirements; and any changes or additions to special permit conditions.
G.2	Submission of a request for renewal meeting the requirements in S.C. Regulation 61-62.1, Section II.H, shall allow the owner/operator to continue operating pursuant to the most recent general conditional major operating permit, until such time as the Department has taken final action on the request for renewal.
G.3	This permit may be reopened by the Department for cause or to include any new standard or regulation which becomes applicable to a source during the life of the permit.
G.4	This permit may be modified by the Department for cause, to include any applicable requirement or to add or alter a permit's expiration date.
G.5	(S.C. Regulation 61-62.1, Section II.M) Within 30 days of the transfer of ownership/operation of a facility, the current permit holder and prospective new owner/operator shall submit to the Director of Engineering Services a written request for transfer of the source operating or construction permits. The written request for transfer of the source operating or construction permit shall include any changes pertaining to the facility name and mailing address; the name, mailing address, and telephone number of the owner/operator for the facility; and any proposed changes to the permitted activities of the source. Transfer of the operating or construction permits will be effective upon written approval by the Department.

H. GENERAL CONDITIONS

Condition Number	Condition
H.1	The owner or operator shall comply with S.C. Regulation 61-62.2 "Prohibition of Open Burning."
H.2	The owner or operator shall comply with S.C. Regulation 61-62.3 "Air Pollution Episodes."
H.3	The owner or operator shall comply with S.C. Regulation 61-62.4 "Hazardous Air Pollution Conditions."

ASPHALT PLANTS
Page 19 of 19

H. GENERAL CONDITIONS

Condition Number	Condition
H.4	This permit only covers emission units and control equipment while physically present at the indicated facility. Unless the permit specifically provides for the equipment relocation, this permit is void for an item of equipment on the day it is removed from the permitted facility, notwithstanding the expiration date specified on the permit.
H.5	The permittee shall pay permit fees to the Department in accordance with the requirements of S.C. Regulation 61-30, Environmental Protection Fees.
H.6	<p>In the event of an emergency, as defined in S.C. Regulation 61-62.1, Section II.L, the owner or operator may document an emergency situation through properly signed, contemporaneous operating logs, and other relevant evidence that verify:</p> <ol style="list-style-type: none"> 1. An emergency occurred, and the owner or operator can identify the cause(s) of the emergency; 2. The permitted source was at the time the emergency occurred being properly operated; 3. During the period of the emergency, the owner or operator took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements in the permit; and 4. The owner or operator gave a verbal notification of the emergency to the Department within 24 hours of the time when emission limitations were exceeded, followed by a written report within 30 days. The written report shall include, at a minimum, the information required by S.C. Regulation 61-62.1, Section II.J.1.c.i through viii. The written report shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken. <p>This provision is in addition to any emergency or upset provision contained in any applicable requirement.</p>
H.7	<p>(S.C. Regulation 61-62.1, Section II.O) Upon presentation of credentials and other documents as may be required by law, the owner or operator shall allow the Department or an authorized representative to perform the following:</p> <ol style="list-style-type: none"> 1. Enter the facility where emissions-related activity is conducted, or where records must be kept under the conditions of the permit. 2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. 3. Inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit. 4. As authorized by the Federal Clean Air Act and/or the S.C. Pollution Control Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit or applicable requirements.