



**Line Report: Proposed Baseline and Setback Line
Litchfield Beach & Huntington Beach State Park
October 6, 2017**

Background

South Carolina Code of Laws §48-39-280, as amended, requires the Department of Health and Environmental Control's Office of Ocean and Coastal Resource Management (OCRM or Department) to establish and periodically review the position of the two lines of beachfront jurisdiction (the baseline and the setback line) once every seven to ten years. For all oceanfront land that is developed or potentially could be developed, the average annual shoreline change rate, also known as the average long-term erosion rate, is also reviewed during this timeframe. The purpose of these jurisdictional lines is to implement §48-39-280(A), which states:

"A forty-year policy of retreat from the shoreline is established. The department must implement this policy and utilize the best available scientific and historical data in the implementation. The department must establish a baseline which parallels the shoreline for each standard erosion zone and each inlet erosion zone. Subject to Section 48-39-290(D), the baseline established pursuant to this section must not move seaward from its position on December 31, 2017."

The baseline is the more seaward of the two jurisdictional lines. Seaward of the baseline, permitted activities are limited to wooden walkways, small wooden decks, fishing piers, golf courses, normal landscaping, groins, activities authorized by emergency orders, beach renourishment projects, and structures authorized by a special permit. The setback line is the landward line of beachfront jurisdiction. Between the baseline and setback line, the Department exercises regulatory permitting authority for such activities as habitable structures and associated infrastructure, decks, gazebos, other public access structures, and sand dune management. Seaward of the setback line, construction of new shore-parallel erosion control structures (i.e. seawalls, revetments or bulkheads) is prohibited. However, existing erosion control structures may be maintained or repaired with prior authorization by the Department.¹

As part of the process of delineating these jurisdictional lines, the Department has collected beach survey data statewide since 1988 at monitoring stations that are typically spaced 2,000 feet apart. Sections of the coast that are not likely to be developed, such as Cape Romain National Wildlife Refuge, are not surveyed. Surveys begin landward of the primary oceanfront sand dune, if one exists, and extend down the beach and offshore. In addition to this beach erosion monitoring data, the Department utilizes recent dune field topographic data such as Light Detection and Ranging (LIDAR), elevation measurements collected with a survey-grade GPS unit, vegetation measurements collected with a mapping-grade GPS unit, current and historical aerial photographs dating back at least 40 years that show the shoreline location, and previous shoreline change analysis data or reports. These data were viewed and analyzed using ESRI's Geographic Information System (GIS) software.

¹ S.C. Code Ann. §48-39-290(A).

Process for Establishing the Baseline Position

To establish the baseline position, the shoreline must first be classified as an inlet zone or a standard zone. Areas that are close to inlets with non-parallel offshore bathymetric contours and non-parallel historical shoreline positions are classified as inlet zones, while all other areas are classified as standard zones. Inlet zone classifications are further refined as either unstabilized, or stabilized by jetties, groins, or seawalls.

In stabilized inlet zones and standard zones, the baseline is located at the crest of the primary oceanfront sand dune using beach survey data or dune field topographic data such as LIDAR. The primary oceanfront sand dune is defined as a dune with a minimum height of 3 feet, as measured vertically from the crest to the toe of the dune. This dune must also form a continuous line for 500 shore parallel feet.² If the shoreline has been altered naturally or artificially by the construction of erosion control devices, groins, or other man-made alterations, the baseline must be established where the crest of the primary oceanfront sand dune would be located if the shoreline had not been altered.³

To calculate a dune crest position at an armored⁴ location, the volume of sand on the beach seaward of the erosion control structure is determined from survey data and then compared to the volume of sand from a nearby unarmored reference profile that displays a representative sand dune. The reference profile is overlaid on the armored profile in such a way that the measured sand volumes match, and then the dune crest position can be transferred from the reference profile to the armored profile. This calculated dune crest position then becomes the baseline.

In unstabilized inlet zones, the baseline is established at the most landward shoreline position at any time during the past 40 years, unless the best available scientific and historical data of the inlet and adjacent beaches indicate that the shoreline is unlikely to return to its former position. This baseline position is established by analyzing shorelines created from historical aerial photographs or shoreline data collected in the field, and identifying the most landward shoreline position.⁵

Process for Establishing the Setback Line Position

The setback line position is dependent on the baseline position and the average annual shoreline change rate, also known as the average long-term erosion rate. The shoreline change rate is calculated using available historical shoreline data and GIS software. The setback line is established landward of the baseline a distance which is 40 times the average annual shoreline change rate or not less than 20 feet.⁶

During this line review, the shoreline change rate calculation was performed using AMBUR (Analyzing Moving Boundaries using R), a tool available through the R-forge statistical environment. Shoreline change analysis was performed every 200 feet. Once the shoreline change rates were calculated, they were analyzed and grouped using the ESRI ArcGIS spatial statistics tool called 'Grouping'. The values within each group were averaged to obtain an

² S.C. Code Regs. 30-1(D)(43).

³ S.C. Code Ann. §48-39-280(A)(1).

⁴ S.C. Code Ann. §48-39-250(5).

⁵ S.C. Code Ann. §48-39-280(A)(2).

⁶ S.C. Code Ann. §48-39-280(B).

annual shoreline change rate. This rate was multiplied by 40 to generate the setback distance from the baseline.

Litchfield Beach & Huntington Beach State Park Baseline

Litchfield Beach and Huntington Beach State Park are located in Georgetown County between Midway Inlet to the south and Murrells Inlet to the north.

Southern Unstabilized Inlet Zone Adjacent to Midway Inlet

At the southern end of Litchfield Beach, the sand spit between the mouth of Midway Inlet and the existing development is classified as an unstabilized inlet zone. This area is low-lying with a small dune field, and the baseline in this zone is set at the most landward point of erosion in the last 40 years. Specifically, the baseline is wrapped around the 2016 vegetation just south of the end of Norris Drive. Any land or water areas to the southwest of the wrapped baseline are considered to be located seaward of the baseline.

Central Standard Zone

From the existing development at the southern end of Litchfield Beach north to OCRM Monument 4525 in Huntington Beach State Park, the shoreline is classified as a standard zone. The southern end of the standard zone on Litchfield to approximately 700 feet south of the end of Inlet Point Drive features no continuous primary dune or natural vegetation line. Therefore, in this section of beach, the baseline is set at on the seaward side of Norris Drive. From that point to Topaz Lane, there are no dune features, therefore, the baseline is set at the vegetation line collected by OCRM staff in January 2017. Between Topaz Lane and the northern end of Parker Drive, the baseline is set on the dune crest identified in LIDAR data from 2014 and verified in the field by OCRM staff in November 2016 and January 2017 using survey-grade GPS equipment. In the standard zone of Huntington Beach State Park, the baseline is set on the primary dune crest identified in LIDAR data from 2014.

Northern Stabilized Inlet Zone Adjacent to Murrells Inlet

From OCRM Monument 4525 in Huntington Beach State Park to the south jetty at Murrells Inlet, the shoreline is classified as a stabilized inlet zone. In this zone, the baseline is set on the primary dune crest identified in LIDAR data from 2014. Any land or water areas to the southwest of the wrapped baseline are considered to be located seaward of the baseline.

Litchfield Beach & Huntington Beach State Park Setback Line

The following table identifies average annual shoreline change rates, from south to north.

Location Description	Shoreline Change Rate (ft/year) *	Multiplier	Setback Distance (ft)
North for 307 feet to the south end of Norris Drive	-1.814	40	73
From the south end of Norris Drive north for 194 feet	-0.8407	40	34
Transition north for 194 feet, then north for 2,144 along Norris Drive	-1.5965	40	64
Transition north for 195 feet, then north for 10,491 feet	-0.6684	40	27
Transition north for 196 feet, then north for 199 feet at Summertime Lane	^	N/A	20

Location Description	Shoreline Change Rate (ft/year) *	Multiplier	Setback Distance (ft)
Transition north for 202 feet, then north for 204 feet at Media Lane	-0.6684	40	27
Transition north for 206 feet, then north from Songbird Lane to the north end of Litchfield Beach	^	N/A	20
From the south end of Huntington Beach State Park north for 6,976 feet	^	N/A	20
Transition north for 238 feet, then north for 1,022 feet	-0.9165	40	37
Transition north for 221 feet, then north for 359 feet	-2.2128	40	89
Transition north for 146 feet, then north for 141 feet	-3.3194	40	133
Transition north for 155 feet, then north for 342 feet	-4.5082	40	180
Transition north for 202 feet, then north for 186 feet	-5.7867	40	232
Transition north for 179 feet, then north for 685 feet	-7.1869	40	288
Transition north for 172 feet, then north for 139 feet	-4.3426	40	174
Transition north for 132 feet, then north for 351 feet	-2.3433	40	94
Transition north for 135 feet, then north for 338 feet	-1.094	40	44
Transition north for 206 feet, then north for 489 feet	^	N/A	20

* A negative number indicates erosion.

^ When this symbol is present, it indicates that the minimum setback is required. The shoreline change rate in these areas is between -0.5 and +31.0 ft/year.

Final Product

Once the location of these proposed new beachfront jurisdictional lines is determined, this "line report" is prepared documenting how the new line positions were established. The proposed lines are then released for a 30-day public comment period, and a public hearing is held for public review and comment on the proposed line positions. The proposed lines are also made available for public review on the South Carolina Beachfront Jurisdiction viewer (<https://gis.dhec.sc.gov/shoreline>). Once the lines are adopted as final, the final versions can also be seen on the South Carolina Beachfront Jurisdiction viewer. The line coordinates are also made available on the DHEC web site in a format that allows them to be downloaded and imported into computer-generated plats by surveyors.