



**Line Report: Proposed Baseline and Setback Line
North Myrtle Beach
October 6, 2017**

Background

South Carolina Code of Laws §48-39-280, as amended, requires the Department of Health and Environmental Control's Office of Ocean and Coastal Resource Management (OCRM or Department) to establish and periodically review the position of the two lines of beachfront jurisdiction (the baseline and the setback line) once every seven to ten years. For all oceanfront land that is developed or potentially could be developed, the average annual shoreline change rate, also known as the average long-term erosion rate, is also reviewed during this timeframe. The purpose of these jurisdictional lines is to implement §48-39-280(A), which states:

"A forty-year policy of retreat from the shoreline is established. The department must implement this policy and utilize the best available scientific and historical data in the implementation. The department must establish a baseline which parallels the shoreline for each standard erosion zone and each inlet erosion zone. Subject to Section 48-39-290(D), the baseline established pursuant to this section must not move seaward from its position on December 31, 2017."

The baseline is the more seaward of the two jurisdictional lines. Seaward of the baseline, permitted activities are limited to wooden walkways, small wooden decks, fishing piers, golf courses, normal landscaping, groins, activities authorized by emergency orders, beach renourishment projects, and structures authorized by a special permit. The setback line is the landward line of beachfront jurisdiction. Between the baseline and setback line, the Department exercises regulatory permitting authority for such activities as habitable structures and associated infrastructure, decks, gazebos, other public access structures, and sand dune management. Seaward of the setback line, construction of new shore-parallel erosion control structures (i.e. seawalls, revetments or bulkheads) is prohibited. However, existing erosion control structures may be maintained or repaired with prior authorization by the Department.¹

As part of the process of delineating these jurisdictional lines, the Department has collected beach survey data statewide since 1988 at monitoring stations that are typically spaced 2,000 feet apart. Sections of the coast that are not likely to be developed, such as Cape Romain National Wildlife Refuge, are not surveyed. Surveys begin landward of the primary oceanfront sand dune, if one exists, and extend down the beach and offshore. In addition to this beach erosion monitoring data, the Department utilizes recent dune field topographic data such as Light Detection and Ranging (LIDAR), elevation measurements collected with a survey-grade GPS unit, vegetation measurements collected with a mapping-grade GPS unit, current and historical aerial photographs dating back at least 40 years that show the shoreline location, and previous shoreline change analysis data or reports. These data were viewed and analyzed using ESRI's Geographic Information System (GIS) software.

¹ S.C. Code Ann. §48-39-290(A).

Process for Establishing the Baseline Position

To establish the baseline position, the shoreline must first be classified as an inlet zone or a standard zone. Areas that are close to inlets with non-parallel offshore bathymetric contours and non-parallel historical shoreline positions are classified as inlet zones, while all other areas are classified as standard zones. Inlet zone classifications are further refined as either unstabilized, or stabilized by jetties, groins, or seawalls.

In stabilized inlet zones and standard zones, the baseline is located at the crest of the primary oceanfront sand dune using beach survey data or dune field topographic data such as LIDAR. The primary oceanfront sand dune is defined as a dune with a minimum height of 3 feet, as measured vertically from the crest to the toe of the dune. This dune must also form a continuous line for 500 shore parallel feet.² If the shoreline has been altered naturally or artificially by the construction of erosion control devices, groins, or other man-made alterations, the baseline must be established where the crest of the primary oceanfront sand dune would be located if the shoreline had not been altered.³

To calculate a dune crest position at an armored⁴ location, the volume of sand on the beach seaward of the erosion control structure is determined from survey data and then compared to the volume of sand from a nearby unarmored reference profile that displays a representative sand dune. The reference profile is overlaid on the armored profile in such a way that the measured sand volumes match, and then the dune crest position can be transferred from the reference profile to the armored profile. This calculated dune crest position then becomes the baseline.

In unstabilized inlet zones, the baseline is established at the most landward shoreline position at any time during the past 40 years, unless the best available scientific and historical data of the inlet and adjacent beaches indicate that the shoreline is unlikely to return to its former position. This baseline position is established by analyzing shorelines created from historical aerial photographs or shoreline data collected in the field, and identifying the most landward shoreline position.⁵

Process for Establishing the Setback Line Position

The setback line position is dependent on the baseline position and the average annual shoreline change rate, also known as the average long-term erosion rate. The shoreline change rate is calculated using available historical shoreline data and GIS software. The setback line is established landward of the baseline a distance which is 40 times the average annual shoreline change rate or not less than 20 feet.⁶

During this line review, the shoreline change rate calculation was performed using AMBUR (Analyzing Moving Boundaries using R), a tool available through the R-forge statistical environment. Shoreline change analysis was performed every 200 feet. Once the shoreline change rates were calculated, they were analyzed and grouped using the ESRI ArcGIS spatial statistics tool called 'Grouping'. The values within each group were averaged to obtain an

² S.C. Code Regs. 30-1(D)(43).

³ S.C. Code Ann. §48-39-280(A)(1).

⁴ S.C. Code Ann. §48-39-250(5).

⁵ S.C. Code Ann. §48-39-280(A)(2).

⁶ S.C. Code Ann. §48-39-280(B).

annual shoreline change rate. This rate was multiplied by 40 to generate the setback distance from the baseline.

North Myrtle Beach Baseline

North Myrtle Beach is located in Horry County and includes the City of North Myrtle Beach and Town of Atlantic Beach, from White Point Swash to Hog Inlet.

Standard Zone

Beginning at OCRM Monument 5650E at White Point Swash and extending northeast to OCRM Monument 5895, the shoreline is classified as a standard zone. The standard zone shoreline is heavily developed, with alternating areas of commercial and residential structures. Between 5650E and 5800, the baseline is set along the current 2008 baseline. Between 5800 and 5825E, the baseline is set on the primary dune crest identified in LIDAR data from 2014 and verified in the field by OCRM staff in October 2016 using survey-grade GPS equipment. Between 5825 and 5895, the baseline is set along the current 2008 baseline.

Northern Stabilized Inlet Zone Adjacent to Hog Inlet

Immediately adjacent to Hog Inlet at the northeastern end of North Myrtle Beach, the shoreline is classified as a stabilized inlet zone from OCRM Monument 5895 to the end of the existing beachfront development. In this zone, the baseline is set along the current 2008 baseline, which follows the top of the revetment which wraps the northern end of the beach.

North Myrtle Beach Setback Line

The following table identifies average annual shoreline change rates, from south to north.

Location Description	Shoreline Change Rate (ft/year) *	Multiplier	Setback Distance (ft)
From the south end of North Myrtle at Ocean Creek Drive to 32 nd Avenue N.	^	N/A	20
Transition north for 194 feet, then north for 199 feet	-0.5641	40	23
North for 387 feet to 35 th Avenue N.	^	N/A	20
North for 558 feet to 36 th Avenue N.	-1.1153	40	45
Transition north for 179 feet, then north for 1,272 feet	-1.9227	40	77
Transition north for 225 feet, then north for 1,394 feet	-2.4276	40	97
Transition north for 205 feet, then north for 1,363	^	N/A	20
Transition north for 200 feet, then north for 1,376 feet	-1.2838	40	51
Transition north for 202 feet, then north for 604 feet	-0.7257	40	29
Transition north for 201 feet, then north to the north end of Ocean Boulevard N.	^	N/A	20
North for 135 feet at the north end of Ocean Boulevard N.	-0.7192	40	29
North for 270 feet	-1.4092	40	56
North for 235 feet	-4.3844	40	175
North for 114 feet, then transition north for 123 feet	^	N/A	20

* A negative number indicates erosion.

^ When this symbol is present, it indicates that the minimum setback is required. The shoreline change rate in these areas is between -0.5 and +31.0 ft/year.

Final Product

Once the location of these proposed new beachfront jurisdictional lines is determined, this “line report” is prepared documenting how the new line positions were established. The proposed lines are then released for a 30-day public comment period, and a public hearing is held for public review and comment on the proposed line positions. The proposed lines are also made available for public review on the South Carolina Beachfront Jurisdiction viewer (<https://gis.dhec.sc.gov/shoreline>). Once the lines are adopted as final, the final versions can also be seen on the South Carolina Beachfront Jurisdiction viewer. The line coordinates are also made available on the DHEC web site in a format that allows them to be downloaded and imported into computer-generated plats by surveyors.