

Line Report: Proposed Baseline and Setback Line Isle of Palms October 6, 2017 Revised May 3, 2018 Revised December 18, 2019

Background

South Carolina Code of Laws §48-39-280, as amended, requires the Department of Health and Environmental Control's Office of Ocean and Coastal Resource Management (OCRM or Department) to establish and periodically review the position of the two lines of beachfront jurisdiction (the baseline and the setback line) once every seven to ten years. For all oceanfront land that is developed or potentially could be developed, the average annual shoreline change rate, also known as the average long-term erosion rate, is also reviewed during this timeframe. The purpose of these jurisdictional lines is to implement §48-39-280(A), which states:

"A forty-year policy of retreat from the shoreline is established. The department must implement this policy and utilize the best available scientific and historical data in the implementation. The department must establish a baseline which parallels the shoreline for each standard erosion zone and each inlet erosion zone. Subject to Section 48-39-290(D), the baseline established pursuant to this section must not move seaward from its position on December 31, 2017."

The baseline is the more seaward of the two jurisdictional lines. Seaward of the baseline, permitted activities are limited to wooden walkways, small wooden decks, fishing piers, golf courses, normal landscaping, groins, activities authorized by emergency orders, beach renourishment projects, and structures authorized by a special permit. The setback line is the landward line of beachfront jurisdiction. Between the baseline and setback line, the Department exercises regulatory permitting authority for such activities as habitable structures and associated infrastructure, decks, gazebos, other public access structures, and sand dune management. Seaward of the setback line, construction of new shore-parallel erosion control structures (i.e. seawalls, revetments or bulkheads) is prohibited. However, existing erosion control structures may be maintained or repaired with prior authorization by the Department.¹

As part of the process of delineating these jurisdictional lines, the Department has collected beach survey data statewide since 1988 at monitoring stations that are typically spaced 2,000 feet apart. Sections of the coast that are not likely to be developed, such as Cape Romain National Wildlife Refuge, are not surveyed. Surveys begin landward of the primary oceanfront sand dune, if one exists, and extend down the beach and offshore. In addition to this beach erosion monitoring data, the Department utilizes recent dune field topographic data such as Light Detection and Ranging (LIDAR), elevation measurements collected with a survey-grade GPS unit, vegetation measurements collected with a mapping-grade GPS unit, current and

¹ S.C. Code Ann. §48-39-290(A).

historical aerial photographs dating back at least 40 years that show the shoreline location, and previous shoreline change analysis data or reports. These data were viewed and analyzed using ESRI's Geographic Information System (GIS) software.

Process for Establishing the Baseline Position

To establish the baseline position, the shoreline must first be classified as an inlet zone or a standard zone. Areas that are close to inlets with non-parallel offshore bathymetric contours and non-parallel historical shoreline positions are classified as inlet zones, while all other areas are classified as standard zones. Inlet zone classifications are further refined as either unstabilized, or stabilized by jetties, terminal groins, or other structures.

In stabilized inlet zones and standard zones, the baseline is located at the crest of the primary oceanfront sand dune using beach survey data or dune field topographic data such as LIDAR. The primary oceanfront sand dune is defined as a dune with a minimum height of 3 feet, as measured vertically from the crest to the toe of the dune. This dune must also form a continuous line for 500 shore parallel feet.² If the shoreline has been altered naturally or artificially by the construction of erosion control devices, groins, or other man-made alterations, the baseline must be established where the crest of the primary oceanfront sand dune would be located if the shoreline had not been altered.³

To calculate a dune crest position at an armored⁴ location, the volume of sand on the beach seaward of the erosion control structure is determined from survey data and then compared to the volume of sand from a nearby unarmored reference profile that displays a representative sand dune. The reference profile is overlaid on the armored profile in such a way that the measured sand volumes match, and then the dune crest position can be transferred from the reference profile to the armored profile. This calculated dune crest position then becomes the baseline.

In unstabilized inlet zones, the baseline is established at the most landward shoreline position at any time during the past 40 years, unless the best available scientific and historical data of the inlet and adjacent beaches indicate that the shoreline is unlikely to return to its former position. This baseline position is established by analyzing shorelines created from historical aerial photographs or shoreline data collected in the field, and identifying the most landward shoreline position.⁵

Process for Establishing the Setback Line Position

The setback line position is dependent on the baseline position and the average annual shoreline change rate, also known as the average long-term erosion rate. The shoreline change rate is calculated using available historical shoreline data and GIS software. The setback line is established landward of the baseline a distance which is 40 times the average annual shoreline change rate or not less than 20 feet.⁶

² S.C. Code Regs. 30-1(D)(43).

³ S.C. Code Ann. §48-39-280(A)(1).

⁴ S.C. Code Ann. §48-39-250(5).

⁵ S.C. Code Ann. §48-39-280(A)(2).

⁶ S.C. Code Ann. §48-39-280(B).

During this line review, the shoreline change rate calculation was performed using AMBUR (Analyzing Moving Boundaries using R), a tool available through the R-forge statistical environment. Shoreline change analysis was performed every 200 feet. Once the shoreline change rates were calculated, they were analyzed and grouped using the ESRI ArcGIS spatial statistics tool called 'Grouping'. The values within each group were averaged to obtain an annual shoreline change rate. This rate was multiplied by 40 to generate the setback distance from the baseline.

Isle of Palms Baseline

Isle of Palms is in Charleston County between Sullivan's Island and Breach Inlet to the southwest and Dewees Inlet and Dewees Island to the northeast.

Southern Unstabilized Inlet Zone Adjacent to Breach Inlet

At the southwestern end of the island, an unstabilized inlet zone extends from the Breach Inlet Bridge to OCRM Monument 3115 at 6th Avenue. In this zone, the baseline is set at the most landward point of erosion in the last 40 years. Specifically, the baseline is set at the vegetation line position collected by OCRM staff in November 2016, and an historical vegetation line position from 1977.

Central Standard Zone

Between OCRM Monument 3115 at 6th Avenue and OCRM Monument 3155 at 47th Avenue, the shoreline is classified as a standard zone. In this zone, the baseline is set on the primary dune crest identified in LIDAR data from 2010 and verified in the field by OCRM staff in July and November 2016 using survey-grade GPS equipment.

Northern Unstabilized Inlet Zone Adjacent to Dewees Inlet

At the northeastern end of the island between OCRM Monument 3155 at 47th Avenue and Dewees Inlet, the shoreline is classified as an unstabilized inlet zone. In this zone, the baseline is set at the most landward point of erosion in the last 40 years. Specifically, the baseline position is comprised of vegetation line data collected by OCRM staff in November 2016, a wet/dry shoreline from 1983, and historical vegetation line positions from 1959, 1967, 1977, 1998, 2008 (2008 baseline position) and 2011. The 1959 and 1967 historical vegetation lines are more than 40 years old, but they were retained in the dataset because of the significant shoreline variability within Wild Dunes and the relative likelihood that the shoreline will return to these former positions in the future. Where the baseline wraps at the northern end of the unstabilized inlet zone adjacent to Dewees Inlet, any land or water areas to the north of the wrapped baseline are located seaward of the baseline.

Isle of Palms Setback Line

The following table identifies average annual shoreline change rates, from south to north.

Location Description	Shoreline Change Rate (ft/year) *	Multiplier	Setback Distance (ft)
From the south end of Isle of Palms to Seagrove Lane	^	N/A	20
Transition north for 191 feet, then north for 732 feet	-1.0233	40	41

Location Description	Shoreline Change Rate (ft/year) *	Multiplier	Setback Distance (ft)
Transition north for 175 feet, then north for 5,776 feet to the south end of Ocean Point Drive	^	N/A	20
Transition north for 84 feet, then north for 308 feet along Ocean Point Drive	-0.785	40	31
Transition north for 120 feet, then north for 795 feet along Ocean Point Drive	^	N/A	20
Transition for north 178 feet, then continuing for 181 feet along Ocean Point Drive	-0.9126	40	37
Transition north for 182 feet, then continuing for 167 feet along Ocean Point Drive	-2.0851	40	83
Transition north for 166 feet, then continuing for 163 feet	-2.7808	40	111
Transition north for 163 feet, then continuing for 606 feet	-3.5353	40	141

* A negative number indicates erosion.

^ When this symbol is present, it indicates that the minimum setback is required. The shoreline change rate in these areas is between -0.5 and +31.0 ft/year.

Final Product

Once the location of these proposed new beachfront jurisdictional lines is determined, this "line report" is prepared documenting how the new line positions were established. The proposed lines are then released for a 30-day public comment period, and a public hearing is held for public review and comment on the proposed line positions. The proposed lines are also made available for public review on the South Carolina Beachfront Jurisdiction viewer (https://gis.dhec.sc.gov/shoreline). Once the lines are adopted as final, the final versions can also be seen on the South Carolina Beachfront Jurisdiction viewer. The line coordinates are also made available on the DHEC web site in a format that allows them to be downloaded and imported into computer-generated plats by surveyors.

Addendum 1

Act # 173 of 2018 known as the "Beachfront Management Reform Act" was signed into law on May 3, 2018 by Governor Henry McMaster. In accordance with the Act, the state's beachfront jurisdictional lines, administered by DHEC's Office of Ocean and Coastal Resource Management, have been established for all beachfront areas of the state as follows.

The baseline is established at the most seaward position of either the current baseline set during the 2008 through 2012 cycle; or the baseline proposed by the department on October 6, 2017.

The setback line is established at the most seaward position of either the current setback line set during the 2008 through 2012 cycle; or the setback line proposed by the department on October 6, 2017.

These jurisdictional lines will be in effect until the completion of the establishment cycle initiating on or after January 1, 2024.

Additional information including survey packets with coordinates is available through the DHEC State Beach Jurisdictional Lines web page at: <u>www.scdhec.gov/beachfrontlines</u>

Addendum 2: December 2019

The shoreline change rates, also known as the long term erosion rates (LTER), provided above, are based on distances along the beach from south to north. The above shoreline change rates only include the erosional areas along a beach that have a setback distance greater than the minimum of 20 feet. Shoreline change rates for all areas (erosional and accretional) are now available through DHEC OCRM's Beachfront Jurisdictional Lines web application (<u>https://gis.dhec.sc.gov/shoreline/</u>). Shoreline change rates for specific segments of the beach can be obtained by locating and clicking on the setback line within the web application. Additional instructions are provided within the web application.

Please note that for the 2016-2018 jurisdictional line review cycle, the baselines and setback lines were established by Act 173 of 2018. The setback line is typically established landward of the baseline a distance of 40 times the shoreline change rate (or long term erosion rate). However, the setback distance established by Act 173 may not reflect the published shoreline change rate.