



SCDHEC's Bureau of Water and Bureau of Environmental Services work to ensure that the water in South Carolina is safe for drinking and recreation, and that it is suitable to support and maintain aquatic flora and fauna. Functions include planning, permitting, compliance assurance, enforcement, and monitoring. This section provides an overview of water quality evaluation and protection activities.

Surface Water Monitoring

In an effort to evaluate the State's water quality, the Department operates and collects data from a statewide network of ambient monitoring sites. The ambient monitoring network is directed toward determining long-term water quality trends, assessing attainment of water quality standards, identifying locations in need of additional attention, and providing background data for planning and evaluating stream classifications and standards.

Ambient monitoring data are also used in the process of formulating permit limits for wastewater discharges with the goal of maintaining State and Federal water quality standards and criteria in the receiving streams in accordance with the goals of the Clean Water Act. These standards and criteria define the instream chemical concentrations that provide for protection and reproduction of aquatic flora and fauna, help determine support of the classified uses of each waterbody, and serve as instream limits for the regulation of wastewater discharges or other activities. In addition, by comparing the ambient monitoring network data to the State Water Quality Standards, these data are used in the preparation of the biennial §305(b) report to Congress, which provides a general summary of statewide water quality, and the §303(d) list of impaired waters with respect to attainment of classified uses.

There are several major components to SCDHEC's ambient surface water quality monitoring activities, including ongoing fixed-location monitoring, cyclic watershed monitoring, and statewide statistical survey monitoring, each designed to provide data for water quality assessment of major water resource types at different spatial and temporal scales. In addition to sites sampled specifically as part of the discontinued cyclical watershed activities (W), the ambient surface water quality monitoring program includes several different monitoring station types: Integrator (INT), and Base sites (BASE), Special Purpose (SPRP), Survey Stream for year ## (RS##), Survey Lake for year ## (RL##), Survey Tide Creek for year ## (RT##), Survey Open Water for year ## (RO##), biological (BIO) stations.

Integrator Sites were fixed-location sites sampled on a monthly basis, year-round, every year, that targeted the furthest downstream access of each of the 10-digit watershed units in the state, as well as the major waterbodies that occurred within these watershed units. Base Sites replaced Integrator Sites when funding reductions reduced the monitoring frequency to only every other month (bi-monthly). Special Purpose Sites are permanent, monthly or bi-monthly, year-round, fixed-location sites, but represent locations of special interest to the Department that do not meet the location criteria of Integrator Sites.

Watershed stations (W) were sampled on a monthly basis, year-round, during a basin's target year. Funding reductions have forced the elimination of this monitoring component. Watershed stations were located to provide a more complete and representative coverage within the larger drainage basin, and to identify additional monitoring needs. Watershed stations had the same parameter coverage as

Integrator and Base Sites. Watershed stations were locations with extensive historic monitoring data. Changes in water quality could be identified by comparison of the new data to the historic data.

A statewide Statistical Survey component is part of the monitoring design. A statistical survey monitoring design is a type of survey design in which the population of interest is sampled in such a manner that allows statements to be made about the whole population based on a subsample, and produces an estimate of the accuracy of the assessment results. The advantage of the statistical survey sampling design is that statistically valid statements about water quality can be made about large areas based on a relatively small subsample. Separate monitoring schemes have been developed for stream, lake/reservoir, and estuarine resources. Each year a new statewide set of statistical survey sites is selected for each waterbody type. Survey Sites are sampled on a monthly basis for one year with the same parameter coverage as Integrator or Base Sites. The data from those Survey Sites located within this basin are included in this assessment.

Ambient biological trend monitoring is conducted to collect data to indicate general biological conditions of State waters that may be subject to a variety of point and nonpoint source impacts. Ambient biological sampling is also used to establish regional reference or "least impacted" sites from which to make comparisons in future monitoring. Additionally, special macroinvertebrate studies, in which stream specific comparisons among stations located upstream and downstream from a known discharge or nonpoint source area, are used to assess impact.

Qualitative sampling of macroinvertebrate communities is the primary bioassessment technique used in ambient biological trend monitoring. A habitat assessment of general stream habitat availability and a substrate characterization is conducted at each site. Annual ambient biological monitoring is conducted during low flow "worst case" conditions in July - September. Some coastal plain streams that have no flow conditions in the summer months may be sampled in the winter (January-March). This technique may also be used in special studies for the purpose of determining if, and to what extent, a wastewater discharge or nonpoint source runoff is impacting the receiving stream. A minimum of two sample locations, one upstream and one downstream from a discharge or runoff area, is collected. At least one downstream recovery station is also established when appropriate. Sampling methodology follows procedures described in Standard Operating Procedures, Biological Monitoring. Only sites described as "BIO" will collect information on the macroinvertebrate communities used in the ambient biological trend monitoring.

Many pollutants may be components of point source discharges, but may be discharged in a discontinuous manner, or at such low concentrations that water column sampling for them is impractical. Some pollutants are also common in nonpoint source runoff, reaching waterways only after a heavy rainfall; therefore, in these situations, the best media for the detection of these chemicals are sediment and fish tissue where they may accumulate over time. Their impact may also affect the macroinvertebrates.

Natural Swimming Areas

Although all waters of the State are protected for swimming, some areas are more popular than others and may require closer monitoring. Currently monitored areas have been located on the GIS map in the appropriate watersheds.

Classified Waters, Standards, and Natural Conditions

The waters of the State have been classified in regulation based on the desired uses of each waterbody. State standards for various parameters have been established to protect all uses within each classification. The water-use classifications that apply to this basin are as follows.

Class ORW, or "outstanding resource waters", are freshwaters or saltwaters that constitute an outstanding recreational or ecological resource, or those freshwaters suitable as a source for drinking water supply purposes, with treatment levels specified by the Department.

Class FW, or "freshwaters", are freshwaters that are suitable for primary and secondary contact recreation and as a source for drinking water supply, after conventional treatment, in accordance with the requirements of the Department. These waters are suitable for fishing, and the survival and propagation of a balanced indigenous aquatic community of fauna and flora. This class is also suitable for industrial and agricultural uses.

Class SFH, or "shellfish harvesting" waters, are tidal saltwaters protected for shellfish harvesting, and are suitable also for uses listed in Classes SA and SB.

Class SA comprises "tidal saltwaters" suitable for primary and secondary contact recreation, crabbing and fishing. These waters are not protected for harvesting of clams, mussels, or oysters for market purposes or human consumption. The waters are suitable for the survival and propagation of a balanced indigenous aquatic community of marine fauna and flora.

Class SB are "tidal saltwaters" suitable for the same uses listed in SA. The difference between the Class SA and SB saltwater concerns the DO limitations. Class SA waters must maintain daily DO averages not less than 5.0 mg/l, with a minimum of 4.0 mg/l, and Class SB waters maintain DO levels not less than 4.0 mg/l.

Class GB, or "groundwaters", include all groundwaters of the State, unless classified otherwise, which meet the definition of underground sources of drinking water.

Site specific numeric standards (*) for surface waters may be established by the Department to replace the numeric standards found in Regulation 61-68 or to add new standards not contained in R.61-68. Establishment of such standards shall be subject to public participation and administrative procedures for adopting regulations. In addition, such site specific numeric standards shall not apply to tributary or downstream waters unless specifically described in the water classification listing in R.61-69.

The standards are used as instream water quality goals to maintain and improve water quality and also serve as the foundation of the Bureau of Water's program. They are used to determine permit limits for treated wastewater dischargers and any other activities that may impact water quality. Using mathematical Wasteload Allocation Models, the impact of a wastewater discharge on a receiving stream is predicted under critical conditions following R.61-68. These predictions are then used to set limits for different pollutants on the National Pollutant Discharge Elimination System (NPDES) permits issued by the Department. The NPDES permit limits are set so that, as long as a permittee (wastewater discharger) meets the established permit limits, the discharge should not cause a standards violation in the receiving stream. All discharges to the waters of the State are required to have an NPDES permit and must abide by those limits, under penalty of law.

Classifications are based on desired uses, not on natural or existing water quality, and are a legal means to obtain the necessary treatment of discharged wastewater to protect designated uses. Actual water quality may not have a bearing on a waterbody's classification. A waterbody may be reclassified if desired or existing public uses justify the reclassification and the water quality necessary to protect these uses is attainable. A classification change is an amendment to a State regulation and requires public participation, SCDHEC Board approval, and General Assembly approval.

Natural conditions may prevent a waterbody from meeting the water quality goals as set forth in the standards. The fact that a waterbody does not meet the specified numeric standards for a particular classification does not mean the waterbody is polluted or of poor quality. Certain types of waterbodies (i.e. swamps, lakes, tidal creeks) may naturally have water quality lower than the numeric standards. A waterbody can have water quality conditions below standards due to natural causes and still meet its use classification. A site specific numeric standard may be established by the Department after being subjected to public participation and administrative procedures for adopting regulations. Site specific numeric standards apply only to the stream segment described in the water classification listing, not to tributaries or downstream unspecified waters.

Water Quality Indicators

Water quality data are used to describe the condition of a waterbody, to help understand why that condition exists, and to provide some clues as to how it may be improved. Water quality indicators include physical, chemical, and biological measurements. The current State of S.C. Monitoring Strategy describes what parameters are sampled, where they are sampled, and how frequently. It is available on our website at <http://www.scdhec.gov/HomeAndEnvironment/Docs/Strategy.pdf>

MACROINVERTEBRATE COMMUNITY

Macroinvertebrates are aquatic insects and other aquatic invertebrates associated with the substrates of waterbodies (including, but not limited to, streams, rivers, tidal creeks, and estuaries). Macroinvertebrates can be useful indicators of water quality because these communities respond to integrated stresses over time that reflect fluctuating environmental conditions. Community responses to various pollutants (i.e. organic, toxic, and sediment) may be assessed through interpretation of diversity, known organism tolerances, and in some cases, relative abundances and feeding types.

FISH TISSUE

Many pollutants occur in such low concentrations in the water column that they are usually below analytical detection limits. Over time many of these chemicals may accumulate in fish tissue to levels that are easily measured. By analyzing fish tissue it is possible to see what pollutants may be present in waterbodies at very low levels. This information can also be used to determine if consumption of the fish poses any undue human health concerns and to calculate consumption rates that are safe.

DISSOLVED OXYGEN

Oxygen is essential for the survival and propagation of aquatic organisms. If the amount of oxygen dissolved in water falls below the minimum requirements for survival, aquatic organisms or their eggs and larvae may die. A severe example is a fish kill. Dissolved oxygen (DO) varies greatly due to

natural phenomena, resulting in daily and seasonal cycles. Different forms of pollution also can cause declines in DO.

Changes in DO levels can result from temperature changes or the activity of plants and other organisms present in a waterbody. The natural diurnal (daily) cycle of DO concentration is well documented. Dissolved oxygen concentrations are generally lowest in the morning, climbing throughout the day due to photosynthesis and peaking near dusk, then steadily declining during the hours of darkness.

There is also a seasonal DO cycle in which concentrations are greater in the colder, winter months and lower in the warmer, summer months. Streamflow (in freshwater) is generally lower during the summer and fall, and greatly affects flushing, reaeration, and the extent of saltwater intrusion, all of which affect dissolved oxygen values.

BIOCHEMICAL OXYGEN DEMAND

Five-day biochemical oxygen demand (BOD₅) is a measure of the amount of dissolved oxygen consumed by the decomposition of carbonaceous and nitrogenous matter in water over a five-day period. The BOD₅ test indicates the amount of biologically oxidizable carbon and nitrogen that is present in wastewater or in natural water. Matter containing carbon or nitrogen uses dissolved oxygen from the water as it decomposes, which can result in a dissolved oxygen decline. The quantity of BOD₅ discharged by point sources is limited through the National Pollutant Discharge Elimination System (NPDES) permits issued by the Department. The discharge of BOD₅ from a point source is restricted by the permits so as to maintain the applicable dissolved oxygen standard.

pH

pH is a measure of the hydrogen ion concentration of water, and is used to indicate degree of acidity. The pH scale ranges from 0 to 14 standard units (SU). A pH of 7 is considered neutral, with values less than 7 being acidic, and values greater than 7 being basic.

Low pH values are found in natural waters rich in dissolved organic matter, especially in Coastal Plain swamps and black water rivers. The tannic acid released from the decomposition of vegetation causes the tea coloration of the water and low pH. High pH values in lakes during warmer months are associated with high phytoplankton (algae) densities. The relationship between phytoplankton and daily pH cycles is well established. Photosynthesis by phytoplankton consumes carbon dioxide during the day, which results in a rise in pH. In the dark, phytoplankton respiration releases carbon dioxide. In productive lakes, carbon dioxide decreases to very low levels, causing the pH to rise to 9-10 SU.

FECAL COLIFORM BACTERIA

Fecal coliform bacteria are present in the digestive tract and feces of all warm-blooded animals, including humans, poultry, livestock, and wild animal species. Fecal coliform bacteria are themselves generally not harmful, but their presence indicates that surface waters may contain pathogenic microbes. Diseases that can be transmitted to humans through water contaminated by improperly treated human or animal waste are the primary concern. At present, it is difficult to distinguish between waters contaminated by animal waste and those contaminated by human waste.

Public health studies have established correlations between fecal coliform numbers in recreational and drinking waters and the risk of adverse health effects. Based on these relationships, the USEPA and

SCDHEC have developed enforceable standards for surface waters to protect against adverse health effects from various recreational or drinking water uses. Proper waste disposal or sewage treatment prior to discharge to surface waters minimizes this type of pollution.

NUTRIENTS

Oxygen demanding materials and plant nutrients are common substances discharged to the environment by man's activities, through wastewater facilities and by agricultural, residential, and stormwater runoff. The most important plant nutrients, in terms of water quality, are phosphorus and nitrogen. In general, increasing nutrient concentrations are undesirable due to the potential for accelerated growth of aquatic plants, including algae.

The forms of nitrogen routinely analyzed at SCDHEC stations are ammonia and ammonium nitrogen (NH_3/NH_4), total Kjeldahl nitrogen (TKN), and nitrite and nitrate nitrogen (NO_2/NO_3). Ammonia and ammonium are readily used by plants. TKN is a measure of organic nitrogen and ammonia in a sample. Nitrate is the product of aerobic transformation of ammonia, and is the most common form used by aquatic plants. Nitrite is usually not present in significant amounts. Total nitrogen is the sum of TKN and NO_2/NO_3 .

Total phosphorus (TP) is commonly measured to determine phosphorus concentrations in surface waters. TP includes all of the various forms of phosphorus (organic, inorganic, dissolved, and particulate) present in a sample.

CHLOROPHYLL *a*

Nuisance plant growth can create imbalances in the aquatic community, as well as aesthetic and access issues. Invasive growth of rooted aquatic vegetation can clog boat motors and create disagreeable conditions for swimming and water skiing. High densities of microscopic algae (phytoplankton) can cause wide fluctuations in pH and dissolved oxygen, and can cause undesirable shifts in the composition of aquatic life, or even fish kills. Chlorophyll *a* is a dominant photosynthetic pigment in plants and is used as an indicator of the density of phytoplankton in the water column. The process of cultural eutrophication, from increased plant nutrients, is particularly noticeable in lakes. Continuous flushing in streams prevents the development of significant phytoplankton populations and the resultant chemical changes in water quality.

TURBIDITY

Turbidity is an expression of the scattering and absorption of light through water. The presence of clay, silt, fine organic and inorganic matter, soluble colored organic compounds, and plankton and other microscopic organisms increases turbidity. Increasing turbidity can be an indication of increased runoff from land. It is an important consideration for drinking water as finished water has turbidity limits.

TOTAL SUSPENDED SOLIDS

Total Suspended Solids (TSS) are the suspended organic and inorganic particulate matter in water. Although increasing TSS can also be an indication of increased runoff from land, TSS differs from turbidity in that it is a measure of the mass of material in, rather than light transmittance through, a water sample. High TSS can adversely impact fish and fish food populations and damage invertebrate populations. There are no explicit State standards for TSS.

HEAVY METALS

Concentrations of cadmium, chromium, copper, lead, mercury, and nickel in water are routinely measured by the Department to compare to State standards intended to protect aquatic life and human health. These metals occur naturally in the environment, and many are essential trace elements for plants and animals. Human activities, such as land use changes and industrial and agricultural processes have resulted in an increased flux of metals from land to water. Atmospheric inputs are also recognized as important sources of metals to aquatic systems. Metals are released to the atmosphere from the burning of fossil fuels (coal, oil, gasoline), wastes (medical, industrial, municipal), and organic materials. The metals are then deposited on land and in waterways from the atmosphere via rainfall and attached to particulates (dry deposition).

Assessment Methodology

USE SUPPORT DETERMINATION

Physical, chemical and biological data were evaluated, as described below, to determine if water quality met the water quality criteria established to protect the State classified uses defined in S.C. Regulation 61-68, *Water Classifications and Standards* www.scdhec.gov/Agency/docs/water-regs/R.61-68.pdf. Some waters may exhibit characteristics outside the appropriate criteria due to natural conditions. Such natural conditions do not constitute a violation of the water quality criteria. To determine the appropriate classified uses and water quality criteria for specific waterbodies and locations, refer to S.C. Regulation 61-69, *Classified Waters* www.scdhec.gov/Agency/docs/water-regs/R.61-69.pdf, in conjunction with S.C. Regulation 61-68. Monitoring stations that do not meet the standards of the classified uses are placed on the section 303(d) list of impaired waters <http://www.scdhec.gov/HomeAndEnvironment/Water/ImpairedWaters/Overview/>.

At the majority of SCDHEC's surface water monitoring stations, samples for analysis are collected as surface grabs once per month, quarter, or year, depending on the parameter. Grab samples collected at a depth of 0.3 meters are considered to be a surface measurement. For the purpose of assessment, only surface samples are used in standards comparisons and trend assessments. Because of the inability to target individual high or low flow events on a statewide basis these data are considered to represent typical physical conditions and chemical concentrations in the waterbodies sampled. All water and sediment samples are collected and analyzed according to standard procedures (SCDHEC 1997, 2001).

Results from water quality samples can be compared to State and USEPA criteria, with some restrictions due to time of collection and sampling frequency. For certain parameters, the monthly sampling frequency employed in the ambient monitoring network is insufficient for strict interpretation of the standards. The USEPA does not define the sampling method or frequency other than indicating that it should be "representative." The grab sample method is considered to be representative for the purpose of indicating excursions relative to criteria, within certain considerations. A single grab sample is more representative of a one-hour average than a four-day average, more representative of a one-day average than a one-month average, and so on; thus, when inferences are drawn from grab samples relative to criteria, sampling frequency and the intent of the criteria must be weighed. When the sampling method or frequency does not agree with the intent of the particular criterion, any conclusion about water quality should be considered as only an indication of conditions, not as a proven circumstance.

Macroinvertebrate community structure is analyzed routinely, at selected stations, as a means of detecting adverse biological impacts on the aquatic fauna of the state's waters due to water quality conditions that may not be readily detectable in the water column chemistry.

AQUATIC LIFE USE SUPPORT

One important goal of the Clean Water Act, the South Carolina Pollution Control Act, and the State Water Quality Classifications and Standards is to maintain the quality of surface waters to provide for the survival and propagation of a balanced indigenous aquatic community of fauna and flora. The degree to which aquatic life is protected (Aquatic Life Use Support) is assessed by comparing important water quality characteristics and the concentrations of potentially toxic pollutants with numeric criteria.

Support of aquatic life uses is determined based on the percentage of numeric criteria excursions and, where data are available, the composition and functional integrity of the biological community. The term excursion is used to describe a measured pollutant concentration that is outside of the acceptable range as defined by the appropriate criterion. Some waters may exhibit characteristics outside the appropriate criteria due to natural conditions. Such natural conditions do not constitute a violation of the water quality criteria. A number of waterbodies have been given waterbody-specific criteria for pH and dissolved oxygen, which reflect natural conditions. To determine the appropriate numeric criteria and classified uses for specific waterbodies and locations, please refer to S.C. Regulation 61-68, *Water Classifications and Standards* and S.C. Regulation 61-69, *Classified Waters*.

If the appropriate criterion for **dissolved oxygen and pH** are contravened in 10 percent or less of the samples, the criterion is said to be fully supported. If the percentage of criterion excursions is greater than 10 percent, but less than or equal to 25 percent, the criterion is partially supported, unless excursions are due to natural conditions. If there are more than 25 percent excursions, the criterion is not supported, unless excursions are due to natural conditions. The decision that criteria excursions are due to natural conditions is determined by consensus and/or the professional judgment of SCDHEC staff with specific local knowledge.

If the appropriate acute or chronic aquatic life criterion for any individual **toxicant (heavy metals, priority pollutants, ammonia)** is exceeded more than once, representing more than 10 percent of the samples collected, the criterion is not supported. If the acute or chronic aquatic life criterion is exceeded more than once, but in less than or equal to 10 percent of the samples, the criterion is partially supported.

The total recoverable metals criteria for **heavy metals** are adjusted to account for solids partitioning following the approach set forth in the Office of Water Policy and Technical Guidance on Interpretation and Implementation of Aquatic Life Metals Criteria, October 1, 1993, by Martha G. Prothro, Acting Assistant Administrator for Water, available from the Water Resource center, USEPA, 401 M St., SW, mail code RC4100, Washington, DC 20460; and 40CFR 131.36(b)(1). Under this approach, a default TSS value of 1 mg/L is used. Where the metals criteria are hardness based, a default value of 25 mg/L is used for waters where hardness is 25 mg/l or less.

The calculation of the appropriate criterion value for **ammonia** requires the values of several associated field parameters measured concurrent with the ammonia sample collection. Where direct measurements of any of the parameters are lacking the ammonia value will not be used to determine compliance with the standards.

If the appropriate criterion for **turbidity** in all waters, and for waters with **numeric total phosphorus, total nitrogen, and chlorophyll-a** criteria is exceeded in more than 25 percent of the samples, the criterion is not supported. If the criterion is exceeded in more than 10 but less than 25 percent, sites are evaluated on a case-by-case basis to determine if local conditions indicate that classified uses are impaired. Among the characteristics considered are: hydrology and morphometry of the waterbody, existing and projected trophic state, characteristics of pollutant loadings and ongoing pollutant control mechanisms. If the criterion is exceeded in less than 10 percent of the samples, then the criterion is fully supported.

If the conclusion for any single parameter is that the criterion is not supported, then it is concluded that aquatic life uses are not supported for that waterbody, at that monitoring location. If there are no criteria that are not supported, but the conclusion for at least one parameter criterion is partially supported, then the conclusion is aquatic life uses are partially supported. Regardless of the number of samples, no monitoring site will be listed as partially or not supporting for any pollutant based a single sample result because of the possibility of an anomalous event.

The goal of the standards for aquatic life uses is the protection of a balanced indigenous aquatic community; therefore, biological data is the ultimate deciding factor, regardless of chemical conditions. If biological data shows a healthy, balanced community, the use is considered supported even if chemical parameters do not meet the applicable criteria.

MACROINVERTEBRATE DATA INTERPRETATION

Macroinvertebrate community assessment data are used to directly determine Aquatic Life Use Support and to support determinations based on water chemistry data. Macroinvertebrate community data may also be used to evaluate potential impacts from the presence of sediment contaminants. Aquatic and semi-aquatic macroinvertebrates are identified to the lowest practical taxonomic level depending on the condition and maturity of specimens collected. The EPT Index and the North Carolina Biotic Index are the main indices used in analyzing macroinvertebrate data. To a lesser extent, taxa richness and total abundance may be used to help interpret data.

The EPT Index or the Ephemeroptera (mayflies) - Plecoptera (stoneflies) - Trichoptera (caddisflies) Index is the total taxa richness of these three generally pollution-sensitive orders. EPT values are compared with least impacted regional sites. The Biotic Index for a sample is the average pollution tolerance of all organisms collected, based on assigned taxonomic tolerance values. A database is currently being developed to establish significant EPT index levels to be used in conjunction with the Biotic Index to address aquatic life use support.

Taxa richness is the number of distinct taxa collected and is the simplest measure of diversity. High taxa richness is generally associated with high water quality. Increasing levels of pollution progressively eliminate the more sensitive taxa, resulting in lower taxa richness. Total abundance is the enumeration of all macroinvertebrates collected at a sampling location. When gross differences in abundance occur between stations, this metric may be considered as a potential indicator.

RECREATIONAL USE SUPPORT

Recreational use support is defined as the degree to which the swimmable goal of the Clean Water Act is attained and is based on the frequency of fecal coliform bacteria excursions. A fecal

coliform excursion is defined as an occurrence of a bacteria concentration greater than 400/100 ml for all surface water classes. Comparisons to the bacteria geometric mean standard are not considered appropriate based on sampling frequency and the intent of the standard. If 10 percent or less of the samples are greater than 400/100 ml, then recreational uses are said to be fully supported. If the percentage of standards excursions is greater than 10 percent, but less than or equal to 25 percent, then recreational uses are said to be partially supported. If the percentage of excursions is greater than 25 percent, then it is considered to represent nonsupport of recreational uses.

FISH CONSUMPTION USE SUPPORT

The Department uses a risk-based approach to evaluate fish tissue data and to issue consumption advisories in affected waterbodies. This approach contrasts the average daily exposure dose to the reference dose (RfD). Using these relationships, fish tissue data are interpreted by determining the consumption rates that would not be likely to pose a health threat to adult males and nonpregnant adult females. Because an acceptable RfD for developmental neurotoxicity has not been developed, pregnant women, infants, and children are advised to avoid consumption of fish from any waterbody where a mercury advisory was issued.

Fish consumption use support is determined by the occurrence of advisories or bans on consumption for a waterbody. For the support of fish consumption uses, a fish consumption advisory indicates partial use support, a consumption ban indicates nonsupport of uses. Fish consumption advisories are updated annually in the spring. For background information and the most current advisories please visit <http://www.scdhec.gov/FoodSafety/FishConsumptionAdvisories> .

DRINKING WATER USE SUPPORT

Nonattainment of drinking water use is indicated if the median concentration of the ambient surface water data for any pollutant exceeds the appropriate drinking water Maximum Contaminant Level (MCL), based on a minimum of three samples. Where MCLs do not exist, SCDHEC may use or develop other criteria such that pollutant concentrations or amounts do not interfere with drinking water use, actual or intended, as determined by SCDHEC.

Additional Screening and Prioritization Tools

Evaluation of water quality data and other supplemental information facilitates watershed planning. Information from the following sources is used to develop watershed-based protection and prevention strategies.

LONG-TERM TREND ASSESSMENT

As part of the watershed water quality assessments, surface data from each station are analyzed for statistically significant long-term trends using the Seasonal Kendall Test Without Correction (SKWOC) for significant serial correlation, using a program written in-house using SAS. Flows are not available for most stations, and the parametric concentrations are not flow-corrected. Seasonal Kendall's Tau Analysis is used to test for the presence of a statistically significant trend of a parameter, either increasing or decreasing, over a fifteen-year period. It indicates whether the concentration of a given

parameter is exhibiting consistent change in one direction over the specified time period. A two sided test at $p=0.1$ is used to determine statistically significant trends, and the direction of trend. An estimate of the magnitude of any statistically significant trend is calculated.

A rigorous evaluation for trends in time-series data usually includes a test for autocorrelation. The data are not tested for autocorrelation prior to the trend analysis. It is felt that autocorrelation would not seriously compromise a general characterization of water quality trends based on such a long series of deseasonalized monthly samples.

One of the advantages of the seasonal Kendall test is that values reported as being below detection limits (DL) are valid data points in this nonparametric procedure, since they are all considered to be tied at the DL value. When the DL changed during the period of interest, all values are considered to be tied at the highest DL occurring during that period. Since it is possible to measure concentrations equal to the value of the DL, values less than DL are reduced by subtraction of a constant so that they remain tied with each other, but are less than the values equal to the DL. Since fecal coliform bacteria detection limits vary with sample dilution, there is no set DL; therefore, for values reported as less than some number, the value of the number is used.